Tyrone Camarero Specifications

Tyrone

Camerero SS000T3R-11

Key features

- Intel® Atom™ D510 (Pineview-D) (DMI)
- Intel® ICH9R Chipset
- Up to 4GB single channel unbuffered, non-ECC DDR2 667MHz SO-DIMM
- 2x Intel 82574L Gigabit LAN
- 6x SATA (3.0Gbps) Ports RAID 0, 1, 5, 10 (Windows Only)
- 1 (x4) PCI-E (in x16 slot)
- 2 rear USB ports + 3 headers (5 ports) + 1 Type A connector
- · Integrated Matrox G200eW Video
- · Integrated IPMI 2.0







Processor/Cache

Processor Intel® Atom™ D510 processor

Chipset

Intel ICH9R Intel 82574L

System Memory

Memory Capacity Two 200-pin SO-DIMM sockets

Supports up to 4 GB of unbuffered, non-ECC DDR2 667MHz SO-DIMM

(Single Channel)

Expansion Slots

PCI-Express 1 (x4) PCI-Express (in x16 slot)

Integrated On-Board

SATA Intel ICH9R SATA 3.0Gbps Controller

RAID 0, 1, 5, 10 support (Windows Only)

LAN 2x RJ45 LAN portI

Add-on Options

RAID Card Optional

Optical Drive Optional

Front Panel:

LED Indicators Power LED,Hard drive activity LED,2x

Network activity LEDs, System Overheat

LED

Switches Power On/Off button,System Reset button

Drive bays

HDD bays 1 x 3.5" Hard Drive Bays

Power Supply

200W Low Noise AC-DC power supply with PFC

Cooling System

Total of two 4-pin fan headers 2 x fans with tachometer monitoring Status monitor for speed control Status monitor for on / off control Support 3-pin fans (without speed control)Low noise fan speed control Pulse Width Modulated (PWM) fan conn

Form Factor

1U Mini ITX

Height :1.7" (43mm) Width :17.2" (437mm) Depth :9.8" (249mm)

E: info@tyronesystems.com

For more/current product information, visit www.tyronesystems.com