

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS100T3R-48

Key features

- Intel® Core™ i7 / i7 Extreme Edition, and Intel® Xeon® 5600/5500/3600/3500 series (QPI up to 6.4 GT/s)
- Up to 24GB DDR3 1600/1333/1066/800 ECC / non-ECC Un-Buffered DIMM
- 2 (x16) PCI-Express 2.0, 1 (x4) PCI-Express (using x8 slot), 1x 32-bit PCI Slots
- Intel® Dual 82574L Gigabit Ethernet Controller
- Supports nVidia® SLI™ and ATI® CrossfireX™ Technology
- 8 x 3.5" hot-swap SATA Drive Bays
- 865W Low-Noise High Efficiency Cooling-Redundant Power Supply
- Tower or Rackmount
- PWM Fan Speed Control



| Processor/Cache | |
|--|--|
| Processor | Intel® Core™ i7 / i7 Extreme Edition, and Intel® Xeon® 5600/5500/3600/3500 series (QPI up to 6.4 GT/s) |
| System Memory | |
| Supports up to 24 GB 1600 / 1333 / 1066 / 800MHz DDR3 ECC / non-ECC Un-Buffered memory Three Channel memory bus 6 DIMM sockets | |
| Expansion Slots | |
| PCI-Express | 2 (x16) PCI-Express 2.0, 1 (x4) PCI-Express (using x8 slot), 1x 32-bit PCI Slots |
| Integrated On-Board | |
| SATA | Intel ICH10R SATA 3.0Gbps Controller RAID 0, 1, 5, 10 support |
| LAN | 2x RJ45 LAN ports |
| Add-on Options | |
| Raid card | Optional |
| Optical Drive | Optional |
| Front Panel | |
| LED Indicators | Power LED Hard drive activity LED 2x Network activity LEDs System |
| Buttons | Power On/Off button System Reset button |

| Drive bays | |
|---|---|
| HDD bays | 6x SATA Hot-swap Drives 2x Spare Trays |
| Peripheral Bays | 2x 5.25" Peripheral Drive Bay 1x 5.25" Bay For Floppy Drive |
| Power Supply | |
| 865W Low-Noise High Efficiency Cooling-Redundant Power Supply | |
| Cooling System | |
| 2x 8cm Hot-swappable PWM Cooling Fans 1x 9cm Hot-Swappable Rear Exhaust PWM Fan 1x Active heatsink w/ heatpipe | |
| Form Factor | |
| 4U Rackmountable / Tower | |
| Width- 17.2" (437mm), Height- 7.0" (178mm) , Depth – 25.5" (648mm) | |
| <p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p> | |