

Tyrone Camarero Specifications



Camarero SS200T3R-18

Key features

- Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600/1600 v2 family
- Intel® C602 Chipset
- 8x 2.5" Hot-swap drive bays
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 1x PCI-E 3.0 x16 FH expansion slot
- Intel® i350 Dual Port Gigabit
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- SATA2 w/ RAID 0, 1, 10 (R5 option)
- 330W Gold Level Power Supply
- SATA Disk-on-module (DOM) power connector; TPM 1.2 and USB Type A



Processor/Cache	
Processor	Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600/1600 v2 family
Chipset	
	Intel® C602 Chipset
System Memory	
	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM, Up to 256GB DDR3 ECC Registered memory (RDIMM)
Expansion Slots	
PCI-Express	1x PCI-E 3.0 x16 Full-height slot
Integrated On-Board	
SATA	2 SATA3 (6Gbps) & 4 SATA2 (3Gbps) RAID 0, 1, 5, 10 support RAID 0, 1, 10 support
LAN	2x RJ45 LAN ports, 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID card	optional
Optical Drive	None

Front Panel	
LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Universal Information (UID) LED
Buttons	Power On/Off Button, System Reset Button
Drive bays	
HDD bays	8x 2.5" Hot-swap drive bays
Peripheral Bays	None
Power Supply	
	330W Gold Level Power Supply
Cooling System	
	3x 40x28mm 4-pin PWM Cooling Fans
Form Factor	
	1U Rackmount Height 1.7" (43mm), Width 17.2" (437mm), Depth 19.98" (507mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	