

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS2C0T3R-14

Key features

- Single socket H2 (LGA 1155) supports Intel® Xeon® E3-1200 & v2 series, 2nd Gen Core i3 processors
- Intel® C202 PCH Chipset
- 4x 3.5" Hot-swap SATA2 HDDs
- 1x PCI-E 3.0* x8 FHFL slot
- Up to 32GB DDR3 ECC 1333MHz /1600MHz* UDIMMs in 4 sockets
- Intel® 82579LM and 82574L, 2x Gigabit Ethernet LAN ports
- IPMI 2.0 on Dedicated LAN port
- 6x SATA 2.0 with RAID 0, 1, 5, 10
- 350W Gold Level Power Supply
- Disk-on-module (DOM) power connector



Processor/Cache	
Processor	Intel® Xeon® processor E3-1200 & v2 series, Intel® 2nd Gen Core i3 processors
Chipset	
	Intel® C202 PCH chipset
System Memory	
Memory Capacity	4x 240-pin DDR3 DIMM sockets Supports up to 32 GB DDR3 ECC Un-Buffered memory (UDIMM)
Expansion Slots	
PCI-Express	1x PCI-E 3.0* x8 Low-profile slot
Integrated On-Board	
SATA	6x SATA2 (3Gbps) w/ RAID 0, 1, 5, 10
LAN	2x RJ45 LAN ports 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid	Optional
optical drive	Optional

Front Panel	
LED	Power LED, Hard drive activity LED, 2x Network activity LEDs System Overheat LED
Switches	Power On/Off Button
Drive Bays	
HDD bays	4x 3.5" Hot-swap SATA2 HDDs w/ RAID
Peripheral Bays	Optional
Power Supply	
	350W Gold Level Power Supply
Cooling System	
	4x 4cm 12,500 RPM PWM fans
Form Factor	
	1U Rackmount
Height	1.7" (43mm),
Width	17.2" (437mm),
Depth	19.8" (503mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	