

Tyrone Camarero Specifications

Tyrone

Camarero SS2C0T3R1-14

Key features

- Single socket H2 (LGA 1155) supports Intel® Xeon® E3-1200 & v2 series, 2nd Gen Core i3 processors*
- Intel® C202 PCH Chipset
- 4x 2.5" Hot-swap SATA2 HDDs (RAID)
- 1x PCI-E 3.0* x8 FHFL slot
- Up to 32GB DDR3 ECC 1333MHz /1600MHz* UDIMMs in 4 sockets
- Intel® 82579LM and 82574L, 2x Gigabit Ethernet LAN ports
- IPMI 2.0 on Dedicated LAN
- 6x SATA 2.0 with RAID 0, 1, 5, 10
- 330W Gold Level Power Supply
- Disk-on-module (DOM) power connector



Processor/Cache

Processor Intel® Xeon® processor E3-1200 & v2 series, Intel® 2nd Gen Core i3 processors

Chipset

Intel® C202 PCH Chipset

System Memory

Memory Capacity 4x 240-pin DDR3 DIMM sockets Supports up to 32 GB DDR3 ECC Un-Buffered memory (UDIMM)

Expansion Slots

PCI-Express 1x PCI-E 3.0* x8 Full-height Full-length slot

Integrated On-Board

SATA 6x SATA2 (3Gbps) w/ RAID 0, 1, 5, 10
LAN 2x RJ45 LAN ports 1x RJ45 Dedicated IPMI LAN port

Add-on Options

RAID Optional
Optical drive None

Front Panel :

LED Indicators Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED

Switches Power On/Off Button

Drive bays

HDD bays 4x 2.5" Hot-swap SATA2 HDDs with RAID

Peripheral Bays Optional

Power Supply

330W Gold Level Power Supply

Cooling System

3x Cooling Fans

Form Factor

1U Rackmount, Height – 1.7" (43mm), Width - 16.8" (426mm), Depth - 21.95" (558mm)

Email: info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com