

# Tyrone Camarero Specifications



## Camarero SS2C0T6C-32R

### Key features

- Intel® Xeon® processor E3-1200 & v2 series, Intel® 2nd Gen. Core i3 & Intel® Pentium® family processors; socket H2 (LGA 1155)\*\*\*
- 2x 3.5" Hot-swap SATA3 (6 Gbps)
- 1 (x8) PCI-E 3.0\*\*\* low-profile slot
- Up to 32GB DDR3 ECC 1333MHz /1600MHz\*\*\* UDIMMs in 4 sockets
- 2x GbE LAN ports via Micro-LP NIC, 1x Dedicated LAN for IPMI Remote Management
- 4x 8cm Heavy duty fans with optimal cooling zone
- 1620W Redundant 80Plus Platinum Level power supplies



Processor/Cache	
Processor	Intel® Xeon® processor E3-1200 v2/series, Intel® 2nd Gen. Core i3 & Intel® Pentium® family processors***
Chipset	
	Intel® C204 PCH chipset*
System Memory	
Memory Capacity	4x 240-pin DDR3 DIMM sockets
Expansion Slots	
PCI-Express	1 (x8) PCI-E 3.0*** low-profile slot
Integrated On-Board	
SATA	1x SATA DOM 2x SATA 3.0 (6Gbps) w/ RAID 0, 1
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	None

Front Panel :	
LED Indicators	Power LED Node status LED
Switches	Power On/Off Button
Drive bays	
HDD bays	2x 3.5" hot-swap SATA3 (6Gbps) HDDs per node; up to 16 HDDs total Enterprise SATA HDD only recommended
Power Supply	
	1620W Redundant 80Plus Platinum Level power supplies
Cooling System	
	4x 8cm Heavy duty fans with optimal cooling zone
Form Factor	
	3U Rackmount
Height	5.21" (132.5 mm)
Width	17.26" (438.4 mm)
Depth	23.2" (589 mm)
<p><b>E : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	