

# Tyrone Camarero Specifications



Camarero SS2R0T3R-11

## Key features

- Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600/1600 v2 family
- Intel® C602 Chipset
- Up to 2x 3.5" fixed drive bays or up to 4x 2.5" fixed drive bay option
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 1x PCI-E 3.0 x16 FH expansion slot
- Intel® i350 Dual Port Gigabit Ethernet
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- SATA2 w/ RAID 0, 1, 10 (R5 option)
- 350W Gold Level Power Supply
- SATA Disk-on-module (DOM) power connector; TPM 1.2 and USB Type A



Processor/Cache	
Processor	Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600/1600 v2 family
Chipset	
Intel® C602 Chipset	
System Memory	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)
Expansion Slots	
PCI-Express	1x PCI-E 3.0 x16 Full-height slot
Integrated On-Board	
SATA	2 SATA3 (6Gbps) & 4 SATA2 (3Gbps) RAID 0, 1, 5, 10 support (Windows) RAID 0, 1, 10 support (Linux)
LAN	2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	Optional

Front Panel :	
LED Indicators	Power LED HDD drive activity LED 2x Network activity LEDs System Overheat LED
Switches	Power On/Off Button, System Reset Button
Drive bays	
HDD bays	Up to 2x 3.5" fixed drive bays or up to 4x 2.5" fixed drive bay option
Peripheral Bays	Optional
Power Supply	
350W AC power supply w/ PFC	
Cooling System	
2x 40x56mm 4-pin PWM Cooling Fans	
Form Factor	
1U Rackmount	
Height	1.7" (43mm)
Width	17.2" (437mm)
Depth	14.5" (369mm)
<p><b>E : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	