

# Tyrone Camarero Specifications

# Tyrone®

## Camarero SS30012R-34R

### Key features

- Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 and E5-1600 v4/ v3 family
- Intel® C612 chipset
- Up to 1 TB ECC 3DS LRDIMM, upto DDR4- 2400 MHz ; 8x DIMM slots
- 1 PCI-E 3.0 x4 (in x8), 1 PCI-E 3.0 x8 (in x16), 2 PCI-E 3.0 x8, 1 PCI-E 2.0 x2 (in x4), 1 PCI-E 2.0 x4 (in x8)
- Intel @i350-AM2 Dual port GbE LAN
- 10x SATA3 (6Gbps) via C612
- 8x SAS3 (12Gbps) via Broadcom 3008 SW controller; RAID 0, 1, 10
- 1x VGA, 2x COM, 1x TPM
- 4x USB 3.0 ports, 8x USB 2.0 ports
- 2x SuperDOM with built-in power
- 4 x 3.5" fixed drive bay, Optional 4 x 2.5" fixed drive bay.
- 1 x 12cm rear exhaust fan(s), Optional 1 x 12cm (front) cooling fan
- R500W Redundant Power Supply



| Processor/Cache     |   |
|---------------------|---|
| Processor           | Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 and E5-1600 v4/ v3 family             |
| Chipset             |   |
| Chipset             | Intel® C612 chipset   |
| System Memory       |   |
| Memory Capacity     | 8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, Up to 512GB ECC LRDIMM, Up to 256GB ECC RDIMM             |
| Expansion Slots     |   |
| PCI-Express         | 1 PCI-E 3.0 x4 (in x8), 1 PCI-E 3.0 x8 (in x16), 2 PCI-E 3.0 x8, 1 PCI-E 2.0 x2 (in x4), 1 PCI-E 2.0 x4 (in x8) |
| Integrated On-Board |   |
| SATA                | SATA3 (6Gbps) via C612 controller RAID 0, 1, 5, 10 support  |
| SAS                 | SAS3 (12Gbps) via Broadcom 3008 SW RAID 0, 1, 10  |
| LAN                 | 2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port   |
| Add-on Options      |   |
| Optical Drive       | Optional  |
| Front Panel         |   |
| LED Indicators      | 1 Network Activity LEDs, HDD activity LED, Power Status LED, System Information LED                             |
| Buttons             | Power On/Off button   |
| Drive Bays          |   |
| HDD Bays            | 4 x 3.5" fixed drive bay, Optional 4 x 2.5" fixed drive bay   |
| Peripheral Drives   | 2 x standard 5.25" drive bay  |
| Power Supply        |   |
|                     | R500W Redundant Power Supply  |
| Cooling System      |   |
|                     | 1 x 12cm rear exhaust fan(s), Optional 1 x 12cm (front) cooling fan   |
| Form Factor         |   |
| Form Factor         | Mid-Tower   |
| Height              | : 16.7" (424 mm),   |
| Width               | : 7.6" (193 mm),  |
| Depth               | : 20.68" (525 mm)   |

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit

[www.tyronesystems.com](http://www.tyronesystems.com)