

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS300TC-32R

Key features

- Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 & E5-1600v3 family
- Intel® C612 chipset
- 2x 3.5" Hot-swap SATA3/SAS drive bays; SAS requires RAID/HBA AOC
- 1x PCI-E 3.0 x8 LP slot
- Up to 512GB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 4x DIMM slots
- 2x GbE LAN ports via Intel® i350
- 1x Dedicated LAN for IPMI Remote Management
- 4x 8cm Heavy duty fans with optimal cooling zone
- 1620W High-efficiency Redundant Platinum Level power supplies



Processor/Cache		Front Panel	
Processor	Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 & E5-1600 v3 family	LED Indicators	Power LED, Node status LED
Chipset	Intel® C612 chipset	Buttons	Power On/Off button
System Memory		Drive Bays	
Memory Capacity	4x 288-pin DDR4 DIMM slots, Up to 512GB ECC 3DS LRDIMM, Up to 256GB ECC LRDIMM, Up to 128GB ECC RDIMM	HDD bays	2x 3.5" hot-swap SATA3 (6Gbps) HDDs per node; up to 16 HDDs total Enterprise SATA HDD only recommended
Expansion Slots		Power Supply	
PCI-Express	1 (x8) PCI-E 3.0 Low-profile slot	1620W High-efficiency Redundant Platinum Level power supplies	
Integrated On-Board		Cooling System	
SATA	1x SATA DOM, SATA 3.0 (6Gbps) with RAID 0, 1	4x 8cm 11K RPM, 4-pin PWM cooling fans	
LAN:	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Form Factor	
Add-on Options		Form Factor	3U Rackmountable
Raid	Optional	Height :	5.21" (132.5 mm),
Optical Drive	None	Width :	17.26" (438.4 mm),
		Depth :	23.2" (589 mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	