

Tyrone Camarero Specifications



Camarero SS300TL-14R

Key features

- Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 and E5-1600 v3 family
- Intel C612 chipset
- Up to 1TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 8x DIMM slots
- 1PCI-E 3.0 x8
- Intel® i210 Dual port GbE LAN
- SATA3 (6Gbps) via C612
- 1x VGA, 2x COM, 1x TPM
- 4x USB 3.0 ports, 8x USB 2.0 ports
- SuperDOM with built-in power
- 4x 3.5" Hot-swap SAS2 (6Gb/s) / SATA Drive Bays
- 1x Full-height AOC expansion slot
- 4x 40x28mm high-efficiency fans (2 more optional; 6x fans maximum)
- 400W Redundant power supplies



Processor/Cache		Front Panel	
Processor	Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 and E5-1600 v3 family	LED Indicators	Power LED,Hard drive activity LED, 2x Network activity LEDs, System Overheat LED
		Buttons	Power On/Off Button,System Reset Button
Chipset		Drive Bays	
Chipset	Intel C612 chipset	HDD bays	4x 3.5" Hot-swap SAS2 (6Gb/s) / SATA Drive Bays
		Peripheral Drives	1x USB / COM Port tray in slim DVD bay (optional)
System Memory		Power Supply	
Memory Capacity	8x 288-pin DDR4 DIMM slots,Up to 1TB ECC 3DS LRDIMM, Up to 512GB ECC LRDIMM, Up to 256GB ECC RDIMM	400W Redundant power supplies	
Expansion Slots		Cooling System	
PCI-Express	1PCI-E 3.0 x8	4x 40x28mm high-efficiency fans (2 more optional; 6x fans maximum)	
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps) via C612 controller, RAID 0, 1, 5, 10 support	Form Factor	1U Rackmountable
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Width:	17.2" (437 mm),
		Height:	1.7" (43mm)
		Depth:	19.85" (503mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid	Optional		
Optical Drive	Optional		