

# Tyrone Camarero Specifications



## Camarero SS300TR-11T

### Key features

- Intel® Pentium® processor D1508, Single socket FCBGA 1667, 2-Core, 4 Threads, 25W
- Intel® System-on-Chip Design
- 1x 3.5" fixed drive bay or up to 4x 2.5" fixed drive bays
- 1x PCI-E 3.0 x8 slot, M.2 PCIe 3.0, x4, M Key 2242/2280/22110, Mini-PCIe w/ mSATA support
- Up to 128GB ECC RDIMM DDR4 1866MHz or 64GB ECC/non-ECC UDIMM in 4 sockets
- Dual 10G SFP+ and dual 1GbE LAN
- DOM power connector
- 200W Low-noise power supply w/ PFC



Processor/Cache	
Processor	Intel® Pentium® processor D1508, Single socket FCBGA 1667, 2-Core, 4 Threads, 25W
Chipset	
Chipset	Intel® System-on-Chip Design
System Memory	
Memory Capacity	4x DDR4 DIMM sockets, Supports up to 128GB DDR4 ECC RDIMM, Supports up to 64GB DDR4 ECC/non-ECC UDIMM
Expansion Slots	
PCI-Express	1x PCIe 3.0 x8 slots, M.2 PCIe 3.0 x4, M Key 2242/2280 /22110, Mini-PCIe with mSATA support
Integrated On-Board	
SATA	SoC controller for 4 SATA3 (6Gbps) ports; RAID 0,1,5,10 RSTe
LAN	2x 10G SFP+ LAN ports, 2x 1GbE LAN ports, 1x Dedicated IPMI LAN port
Add-on Options	
Raid	Optional
Optical Drive	None

Front Panel	
LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Information LED (temp., status)
Buttons	Power On/Off button, System Reset button
Drive Bays	
HDD bays	1x 3.5" or up to 4x 2.5" Fixed drive bays
Power Supply	
	200W Low-noise power supply w/ PFC
Cooling System	
	1x 40x28mm 13K RPM 4-pin PWM fan
Form Factor	
Form Factor	1U Rackmount
Height	: 1.7" (43mm),
Width	: 17.2" (437mm),
Depth	: 9.8" (249mm)
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	