Tyrone Camarero Specifications


Camarero SS300TR-48R Key features

- Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3, E5-1600 ٠ v4/v3, Core i7Lab ,Astrophysics, Business Intelligence
- Intel[®] C612 chipset
- Up to 512GB ECC DDR4 2400MHz LRDIMM or 128GB ECC/non-ECC UDIMM ٠ (available with Core i7 only);8x DIMM slots
- 4 PCI-E 3.0 x16 (run at 16/16/NA/8 or 16/8/8/8), 2 PCI-E 2.0 x1 (in x4) •
- Intel® i210-AT Dual port GbE LAN .
- 10x SATA3 (6Gbps)
- 1x COM, 1x TPM
- . 8x USB 3.0 ports (6 rear + 2 via header)
- HD Audio 7.1 channel connector by Realtek ALC1150
- . 8x 3.5" SAS/SATA Backplane for Hot-Swappable Drives
- 3x Middle 8cm (5000 rpm) PWM Fans & 2x 8cm (5000 rpm) PWM Fans
- 920W Redundant Platinum Level Certified High-Efficiency Power Supply ٠

Processor/Cache		From
Processor	Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3, E5-1600 v4/ v3, Core i7	LED
Chipset		But
Chipset	Intel [®] C612 chipset	Driv
System Memory		HDI
Memory Capacity	8x 288-pin DDR4 DIMM slots,Up to 1TB ECC 3DS LRDIMM,Up to 512GB ECC LRDIMM, Up to 256GB ECC RDIMM,	Peri
	Up to 128GB DDR4 ECC/non-ECC UDIMM (available with Core i7 only)	Pow
Expansion Slots	920	
PCI-Express	4 PCI-E 3.0 x16 (run at 16/16/NA/8 or 16/8/8/8), 2 PCI-E 2.0 x1 (in x4)	Coo
		3x PW
Integrated On-Board		
		Form
SATA	SATA3 (6Gbps) via C612 controller, RAID 0, 1, 5, 10 support	For
LAN	2x RJ45 Gigabit Ethernet LAN ports	He W De
Add-on Options		
Raid card	Optional	
Optical Drive	Optional	

nt Panel

LED Indicators	2 Network Activity LEDs,Fan Fail/System Over Heat LED,HDD activity LED,Power Status LED		
Buttons	Power On/Off button,System Reset Button		
Drive Bays			
HDD bays	8 x 3.5" hot-swap SAS/SATA drive bay with SGPIO		
Peripheral Drives	1 x 3.5" internal fixed drive bay,2 x standard 5.25" drive bay		
Power Supply			
920W Redundant Platinum Level Certified High-Efficiency Power Supply			
Cooling System			
3x Middle 8cm (5000 rpm) PWM Fans & 2x 8cm (5000 rpm) PWM Fans			
Form Factor			
Form Factor	4U / Full Tower		
-	17.8" (452 mm)		
Width :	7" (178 mm)		
Depth :	25.5" (647 mm)		
Emai	Email : info@tyronesystems.com		
For more/current product information, visit			
www.tyronesystems.com			



O Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries
O Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners





Tyrone