

Tyrone Camarero Specifications

Camarero SS300TR-48RL

Key features

- Single socket R3 (LGA 2011) supports, Intel® Xeon® processor E5-2600, v4/ v3 and E5-1600 v4/ v3 family
- Intel® C612 chipset
- Up to 1TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 8x DIMM slots
- 7x PCI-E slots total: 2 PCI-E 3.0 x8, 2 PCI-E 3.0 x8 (in x16)
- 2 PCI-E 3.0 x8, 2 PCI-E 3.0 x8 (in x16), 2 PCI-E 3.0 x4 (in x8) or 1 x8 + 1 x0, (auto-switch), & 1 PCI-E 2.0 x4 (in x8)
- Intel® i210 Dual port GbE LAN
- 10x SATA3 (6Gbps) via C612
- 1x VGA, 2x COM, 1x TPM
- 4x USB 3.0 ports, 8x USB 2.0 ports
- 2x SuperDOM with built-in power
- 8 x 3.5" hot-swap SAS/SATA drive bay with SGPIO
- 3x Middle 8cm (5000 rpm) PWM Fans & 2x 8cm (5000 rpm) PWM Fans
- 920W Redundant Platinum Level Certified High-Efficiency Power Supply

Tyrone®



Processor/Cache		Front Panel	
Processor	Single socket R3 (LGA 2011) supports, Intel® Xeon® processor E5-2600, v4/ v3 and E5-1600 v4/ v3 family	LED Indicators	2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED
Chipset		Buttons	Power On/Off button, System Reset Button
Chipset	Intel® C612 chipset	Drive Bays	
System Memory		HDD bays	8 x 3.5" hot-swap SAS/SATA drive bay with SGPIO
Memory Capacity	8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, Up to 512GB ECC LRDIMM, Up to 256GB ECC RDIMM	Peripheral Bays	1 x 3.5" internal fixed drive bay, 2 x standard 5.25" drive bay
Expansion Slots		Power Supply	
PCI-Express	2x PCI-E 3.0 x8 (in x16) slots, 2x PCI-E 3.0 x8 slots, 2x PCI-E 3.0 x4 (in x8) slots, Auto-switch to 1 x8 and 1 x0, 1x PCI-E 2.0 x4 (in x8) slot	920W Redundant Platinum Level Certified High-Efficiency Power Supply	
Integrated On-Board		Cooling System	
SATA	SATA3 (6Gbps) via C612 controller, RAID 0, 1, 5, 10 support	3x Middle 8cm (5000 rpm) PWM Fans & 2x 8cm (5000 rpm) PWM Fans	
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Form Factor	
Add-on Options		Form Factor	4U / Full Tower
Raid card	Optional	Height	: 17.8" (452 mm),
Optical Drive	Optional	Width	: 7" (178 mm)
		Depth	: 25.5" (647 mm)
		Email : info@tyronesystems.com	
		For more/current product information, visit www.tyronesystems.com	