

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS300TR-54R

Key features

- High Performance Workstation.
- Designed for 2D/3D Content Creation
- Single socket R3 (LGA 2011) supports ,Intel® Xeon® processor E5-2600 v4/ v3, E5-1600 v4/ v3, Core i7
- Intel® C612 chipset
- Up to 512GB ECC DDR4 2400MHz,LRDIMM or 128GB ECC/non-ECC,UDIMM (available with Core i7 only) 8x DIMM slots
- 4 PCI-E 3.0 x16 (run at 16/16/NA/8 or 16/8/8/8), 2 PCI-E 2.0 x1 (in x4)
- Intel® i210-AT Dual port GbE LAN
- 10x SATA3 (6Gbps)
- 1x COM, 1x TPM
- 8x USB 3.0 ports (6 rear + 2 via header)
- HD Audio 7.1 channel connector by Realtek ALC1150
- 3 x 5.25" bays to 4 x hot-plug SAS/SATA 12G LFF bays
- FSP 550W / 1200W RPS 80Plus Platinum
- Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan



Processor/Cache	
Processor	Single socket R3 (LGA 2011) supports , Intel® Xeon® processor E5-2600 v4/ v3, E5-1600 v4/ v3, Core i7
Chipset	
Chipset	Intel® C612 chipset
System Memory	
Memory Capacity	8x 288-pin DDR4 DIMM slots,Up to 1TB ECC 3DS LRDIMM,Up to 512GB ECC LRDIMM,Up to 256GB ECC RDIMM,Up to 128GB DDR4 ECC/non-ECC UDIMM (available with Core i7 only)
Expansion Slots	
PCI-Express	4 PCI-E 3.0 x16 (run at 16/16/NA/8 or 16/8/8/8), 2 PCI-E 2.0 x1 (in x4)
Integrated On-Board	
SATA	SATA3 (6Gbps) via C612 controller, RAID 0, 1, 5, 10 support
LAN	2x RJ45 Gigabit Ethernet LAN ports
Add-on Options	
Raid Card	Optional
Optical Drive	Optional
Front Panel	
Front Panel	Front Control Panel Power Switch, System Reset
Buttons	Power On/Off button
Drive Bays	
HDD Bays	3 x 5.25" bays to 4 x hot-plug SAS/SATA 12G LFF bays
Peripheral Drives	Optional
Power Supply	
FSP 550W / 1200W RPS , 80Plus Platinum	
Cooling System	
Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan	
Form Factor	
Form Factor	Tower/Convertible/ Rackmount
560 x 200 x 430 mm (22" x 7.9" x 16.9")	
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	