

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

## Camarero SS300TT-32R

### Key features

- Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3/v4, 4th/5th gen. Core™ i3, Pentium, Celeron processors; Socket H3 (LGA 1150)
- Intel® C224 PCH chipset
- 2x 3.5 or 4x 2.5" SATA3 HDDs with Optional kit
- Up to 32GB DDR3 VLP ECC UDIMM 1600/1333MHz support in 4 sockets
- 2x GbE LAN (Intel i350), 1x Dedicated LAN for IPMI Remote Management
- 1x VGA, 1x COM ports, 2x USB 2.0 (with KVM dongle)
- 4x 9cm heavy duty hot-swap fans with optimal cooling zone (per system)
- 1620W Redundant power supplies Platinum Level Certified (per system)



Processor/Cache	
Processor	Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3/v4, 4th/5th gen. Core™ i3, Pentium, Celeron processors; Socket H3 (LGA 1150)
Chipset	
Chipset	Intel® C224 PCH chipset
System Memory	
Memory Capacity	4x 240-pin DDR3 DIMM slots, Supports up to 32 GB DDR3 VLP ECC, Un-Buffered memory (UDIMM)
Expansion Slots	
PCI-Express	1x VGA, 1x COM ports, 2x USB 2.0 (with KVM dongle)
Integrated On-Board	
SATA	1x SATA DOM, 4x SATA3 (6Gbps) w/ RAID 0, 1, 10
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid	Optional
Optical Drive	None

Drive Bays	
HDD Bays (Internal)	2x 3.5" SATA3 HDDs per node; up to 24x 3.5" HDDs total OR 4x 2.5" SATA3 HDDs per node; up to 48x 2.5" HDDs total. Enterprise SATA HDD only recommended
Power Supply	
	1620W Redundant power supplies Platinum Level Certified (per system)
Cooling System	
	4x 9cm Heavy duty fans with optimal cooling zone
Form Factor	
Form Factor	3U Rackmount
Width:	17.5" (444.5 mm),
Height:	5.21" (132.5 mm),
Depth:	29.5" (749.3 mm)
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	