Tyrone Camarero Specifications

Camarero SS300TW-28R

Key features

- Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family
- Intel® C612 chipset
- 8x 3.5" Hot-swap SATA3 drive bays; optional fixed drive bays
- Up to 1TB ECC 3DS LRDIMM, up toDDR4- 2400MHz; 8x DIMM slots
- 5x PCI-E 3.0 x8 slots via riser card
- Intel® i350-AM2 Dual port GbE LAN
- 1x Slim DVD ROM drive bay (option)
- 2x USB 2.0 ports, 2x USB 3.0 ports
- 500W Redundant Power Supplies Platinum Level (94%+)
- 3x middle cooling fans







Processor/Cache

Processor Single socket R3 (LGA 2011) supports

Intel® Xeon® processor E5-2600 v4/ v3

family

Chipset

Chipset Intel® C612 chipset

System Memory

Memory Capacity 8x 288-pin DDR4 DIMM slots,Up to 1TB

ECC 3DS LRDIMM,Up to 512GB ECC LRDIMM,Up to 256GB ECC RDIMM

Expansion Slots

PCI-Express 4x PCI-E 3.0 x8 Full-height Full-length slots,

1x PCI-E 3.0 x8 Low-profile Half-length slot

Integrated On-Board

SATA SATA3 (6Gbps) via C612 controller

RAID 0, 1, 10 support

LAN 2x RJ45 Gigabit Ethernet LAN ports,1x RJ45

Dedicated IPMI LAN port

Add-on Options

RAID Optional

Optical Drive Optional

Front Panel

LED Indicators Power LED, Hard drive activity LED,

2x Network activity LEDs,System

Overheat LED

Buttons Power On/Off button, System Reset button

Drive Bays

HDD bays 8x 3.5" Hot-swap SATA3 drive bays

Power Supply

500W Redundant Power Supplies Platinum Level (94%+)

Cooling System

3x 80x80x38mm 7K RPM Cooling fans

Form Factor

Form Factor 2U Rackmount

width: 17.2" (437mm), Height: 3.5" (88.9mm), Depth: 25.5" (648mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com