

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS3C0TC-32R

Key features

- Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3/v4, 4th/5th gen. Core™ i3, Pentium, Celeron processors; Socket H3 (LGA 1150)
- Intel® C224 PCH chipset
- 2x 3.5" SAS/SATA HDDs
- Up to 32GB DDR3 ECC UDIMM 1600/1333MHz support in 4 sockets
- 2x GbE LAN (Intel i350), 1x Dedicated LAN for IPMI Remote Management
- 1x PCI-E 3.0 x8 and 1x Micro-LP
- 1x VGA, 1x COM ports, 2x USB 2.0 (with KVM dongle)
- 4x 8cm Heavy duty fans with optimal cooling zone
- 1620W High-efficiency Redundant Platinum Level power supplies



Processor/Cache		Front Panel	
Processor	Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3/v4, 4th/5th gen. Core™ i3, Pentium, Celeron processors; Socket H3 (LGA 1150)	LED Indicators	Power LED, Node status LED
Chipset	Intel® C224 PCH chipset	Buttons	Power On/Off button
Memory Capacity		Drive Bays	
Memory Capacity	4x 240-pin DDR3 DIMM slots, Supports up to 32 GB DDR3 ECC, Un-Buffered memory (UDIMM)	HDD bays (Internal)	2x 3.5" hot-swap SATA3 (6Gbps) HDDs per node; up to 16 HDDs total Enterprise SATA HDD only recommended
Expansion Slots		Power Supply	
PCI-Express	1x PCI-E 3.0 x8 and 1x Micro-LP	1620W High-efficiency Redundant Platinum Level power supplies	
Integrated On-Board		Cooling System	
SATA	1x SATA DOM 2x SATA3 (6Gbps) w/ RAID 0 and 1	4x 8cm Heavy duty fans with optimal cooling zone	
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Form Factor	
Add-on Options		Form Factor	3U Rackmountable
Raid	Optional	Height :	5.21" (132.5 mm),
Optical Drive	None	Width :	17.26" (438.4 mm),
		Depth :	23.2" (589 mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	