

Tyrone Camarero Specifications

Camarero SS40012R-18T

Key features

Storage HN, VM, Hosting, Mainstream, Compact File Server

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C236 chipset
- 8 Hot-swap 2.5" SAS/SATA3 Drive Bays
- Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
- 1 PCI-E 3.0 x8 AOC slot
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 2x 10GBase-T ports with Intel® X550
- I/O ports: 1x VGA, 2x COM, 2x USB 3.0 (front/rear), USB 2.0
- 340W High-efficiency Power Supply



Processor/Cache

Processor	Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
-----------	---

Chipset

Chipset	Intel® C236 chipset
---------	---------------------

System Memory

Memory Capacity	Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
-----------------	--

Expansion Slots

PCI Express	1x PCI-E 3.0 x8 AOC slot
-------------	--------------------------

Integrated On-Board

SAS	LSI 3008 SAS3 (12Gbps) controller; SW RAID 0, 1, 10
LAN	2 RJ45 10GBase-T LAN ports, 1 RJ45 Dedicated IPMI LAN port

Add-on Options

Optical Drive	None
---------------	------

Front Panel

LED	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED
Buttons	Power On/Off button, System Reset button

Drive Bays

HDD Bays	8x 2.5" Hot-swap SAS3 drive bays
----------	----------------------------------

Power Supply

340W High-efficiency Power Supply

Cooling System

4x 4cm chassis internal fan

Form Factor

Form Factor	1U Rackmount
Width	17.2" (437mm),
Height	1.7" (43mm),
Depth	19.98" (507mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com