

Tyrone Camarero Specifications

Tyrone

Camarero SS400TR-48RT

Key features



- **High Performance VROC support**
- 2nd Gen Intel® Xeon® Scalable Processors, Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP
- Intel® C622
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
- 1 PCI-E 3.0 x16, 1 PCI-E 3.0 x16 (x16 || x8), 1 PCI-E 3.0 x8 (x0 || x8), 1 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8)
- 2 10GbE LAN ports
- 10 SATA3 (6Gbps) via C622
- I/O: 1 VGA, 2 COM, TPM header
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4 and SATA, Form Factor: 2280, 22110, Key: M-Key, Double Height Connector
- 8 x 3.5"/2.5" hot-swap SAS drive bay with SES3
- 3 x 8cm high-performance PWM fan(s), 2 x 8cm hot-swap exhaust fan(s) & air shroud
- 920W Redundant Platinum Super Quiet power supply W/Pmbus



Processor/Cache		Front Panel	
Processor	2nd Gen Intel® Xeon® Scalable Processors, Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP	LEDs	2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED
Chipset		Buttons	Power On/Off button, System Reset button
Chipset	Intel® C622	Ports	2x USB 2.0 Port(s)
System Memory		Drive Bays	
Memory Capacity	Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots	HDD Bays	8 x 3.5"/2.5" hot-swap SAS drive bay with SES3
Expansion Slots		Peripheral Drives	1 x 3.5" internal fixed drive bay, 2 x standard 5.25" drive bay
PCI-Express	1 PCI-E 3.0 x16, 1 PCI-E 3.0 x16 (x16 x8), 1 PCI-E 3.0 x8 (x0 x8), 1 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8)	Power Supply	
Integrated Onboard		920W Redundant Platinum Super Quiet power supply W/Pmbus	
SATA	Intel® C622 controller for 10 SATA3 (6 Gbps) ports RAID 0,1,5,10	Cooling System	
LAN	2 RJ45 10GBase-T ports	3 x 8cm high-performance PWM fan(s), 2 x 8cm hot-swap exhaust fan(s) & air shroud	
Add-on Options		Form Factor	
Raid Card:	Optional	Form Factor	4U Rackmount
Optical Drive:	Optional	Dimensions	Height : 17.8" (452 mm), Width : 7" (178 mm), Depth : 25.5" (647 mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com