

Tyrone Camarero Specifications

Camarero SS400TR-55L Key features

- Intel® Xeon® W-2100 Processors, Single Socket LGA-2066 (Socket R4) supported, CPU TDP support Up to 140W TDP 18 cores, 36 threads
- Intel® C422
- Up to 256GB ECC RDIMM, DDR4-2666MHz; Up to 512GB ECC LRDIMM, DDR4-2666MHz, in 8 DIMM slots
- 3 PCI-E 3.0 x8,1 PCI-E 3.0 x16,1 PCI-E 3.0 x8 (in x16 slot),1 PCI-E 3.0 x4 (in x8 slot), M.2 Interface: 1 PCI-E 3.0 x4 M.2 Form Factor: 2280/22110, M.2 Key: M-Key, Double Height Connector
- Dual LAN with Intel® i210 Gigabit Ethernet Controller
- Intel® C422 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Drive bays:External:5.25" x 4, 3.5" x 1,Internal: 3.5" or 2.5" x 5
- Front: 120 x 25 mm x1 PWM Fan,Rear: 120 x 25 mm x1 PWM Fan
- 500/1200W Single Power supply ,80 Plus platinum



Processor/Cache

Processor: Intel® Xeon® W-2100 Processors, Single Socket LGA-2066 (Socket R4) supported, CPU TDP support Up to 140W TDP 18 cores, 36 threads

Chipset

Chipset: Intel® C422

System Memory

Memory Capacity: Up to 256GB ECC RDIMM, DDR4-2666MHz; Up to 512GB ECC LRDIMM, DDR4-2666MHz, in 8 DIMM slots

Expansion Slots

PCI-Express: 3 PCI-E 3.0 x8,1 PCI-E 3.0 x16,1 PCI-E 3.0 x8 (in x16 slot),1 PCI-E 3.0 x4 (in x8 slot),M.2 Interface: 1 PCI-E 3.0 x4 M.2 Form Factor: 2280/22110, M.2 Key: M-Key, Double Height Connector

Integrated On-Board

SATA: Intel® C422 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10

LAN: 2 RJ45 Gigabit Ethernet LAN ports

Add-on Options

Raid Card: Optional

Optical Drive: None

Front Panel

LED: Front Control Panel Power Switch, System Rese

Buttons: Power On/Off button

Drive Bays

HDD Drives: 5.25" x 4, 3.5" x 1,Internal: 3.5" or 2.5" x 5

Power Supply

500/1200W Single Power supply ,80 Plus platinum

Cooling System

120 x 25 mm x1 PWM Fan,Rear: 120 x 25 mm x1 PWM Fan

Form Factor

Tower/Convertible/ 5U Rackmount

Dimensions: 560 x 200 x 430 mm (22" x 7.9" x 16.9")

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com