

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS40MTR-34L

Key features

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 165W
- Intel® C621 Chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots;Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- Expansion slots: 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8 (in x8)
- 2 GbE LAN ports
- 12 SATA3 (6Gbps) via C621
- Supports 12V DC power input
- I/O: 1 VGA, 2 COM, TPM header
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4, Form Factor: 2242, 2280, Key: M-Key, Double Height Connector
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays
- 1x Rear 12cm (1850 RPM) PWM Fan
- 500W Bronze Level Certified High-Efficiency Power Supply



Processor/Cache		Front Panel	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 165W	LED	1 Network Activity LEDs, HDD activity LED, Power Status LED, System Overheat LED
Chipset	Intel® C621 Chipset	Buttons	Power On/Off button
System Memory		Drive Bays	
Memory Capacity	Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)	HDD Bays	4 x 3.5" fixed drive bay, Optional 4 x 2.5" fixed drive bay
Expansion Slots	2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8	Peripheral Drives	2 x standard 5.25" drive bay, 1 x 3.5" internal fixed drive bay
Integrated On-Board		Power Supply	
SATA	Intel® C621 controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10	500W Bronze Level Certified High-Efficiency Power Supply	
LAN	2 1GbE LAN ports	Cooling System	
Add-on Options	Raid Card: Optional Optical Drive: Optional	1x Rear 12cm (1850 RPM) PWM Fan	
		Form Factor	
		Form Factor	4U Rackmount
		Height	16.7" (424 mm),
		Width	7.6" (193 mm),
		Depth	20.68" (525 mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	

© Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries.
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners.