

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS4C0TI-12

Key features

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™i7/i5/ i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C236 chipset
- Up to 64GB DDR4 2400MHz ECC/Non-ECC Unbuffered UDIMM; 4 DIMM slots
- 1 PCI-E 3.0 x16
- Dual GbE LAN w/ Intel i219LM + i210AT
- 2 DP, 1 DVI-I, 3 independent displays via Intel HD Graphics, VGA port for BMC
- 4 SATA3 (6Gbps) via C236; RAID 0, 1, 5, 10
- I/O: 1 SATA DOM, 2 COM, TPM 1.2 header, ALC 888S HD Audio
- IPMI, AMT vPro
- Supports 12V DC power input
- 2x 3.5" Fixed Internal Drive Bay
- 2x Counter-rotating Fans
- 350W Gold Level High-efficiency Power Supply



Processor/Cache		Front Panel	
Processor	Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™i7/i5/ i3 series, Intel® Celeron® and Intel® Pentium®	LED Indicators	2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED
Buttons		Buttons	Power On/Off button, System Reset Button
Chipset		Drive Bays	
Chipset	Intel® C236 chipset	HDD bays	2x 3.5" Fixed Internal Drive Bay
		Peripheral Bays	1 x slim DVD-ROM drive bay , Optional 1 x Slim DVD-ROM Drive
System Memory		Power Supply	
Memory Capacity	Up to 64GB DDR4 2400MHz ECC/ Non-ECC Unbuffered UDIMM; 4 DIMM slots		350W Gold Level High-efficiency Power Supply
Expansion Slots		Cooling System	
PCI-Express	1 PCI-E 3.0 x16		2x Counter-rotating Fans
Integrated On-Board		Form Factor	
SATA	Intel® C236 controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10, Intel RSTe	Form Factor	1U Rackmount
LAN	Dual GbE LAN w/ Intel i219LM + i210AT	Height	: 1.7" (43 mm),
		Width	: 17.2" (437 mm),
		Depth	: 14.5" (369 mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid	Optional		
Optical Drive	Optional		