

# Tyrone Camarero Specifications



## Camarero SSA200A2T-24

### Key features

HPC, Cloud Gaming, MEC (Multi-Access Edge Computing), Multi-Purpose CDN, High-availability Cache Cluster, Telco Edge Cloud, EDA (Electric Design Automation), Mission Critical Web Applications

Four hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following:

- Single-Socket, AMD EPYC™ 9004 Series Processors up to 360W TDP
- 12 DIMM Slots , up to 3TB DDR5 memory
- Flexible bays for either Storage or AIOM / OCP 3.0 slots
- Integrated GrandTwin I/O Module with BMC, 2x USB, VGA and 2x 10GbE or 2x 25GbE
- Up to 4 Hot-swap 2.5" NVMe/SATA drives
- Redundant 2200w Titanium Level(96%)High-Efficiency Power Supplies with I2C & PMBus
- 1 per node Air Shroud(s), 2x 17.6K RPM Heavy Duty 8cm Fan(s)



<b>Processor/Cache</b>	Single-Socket, AMD EPYC™ 9004 Series Processors up to 360W TDP Note : Certain CPUs with high TDP may be supported only under specific conditions. Please contact Tyrone Technical Support for additional information about specialized system optimization.
<b>Chipset</b>	AMD SP5
<b>System Memory</b>	Memory Capacity: 12 DIMM slots, Up to 3TB: 12x 256 GB DRAM, Memory Type: 4800MHz ECC DDR5 RDIMM , On-Board Devices (per Node)
<b>Expansion Slots</b>	PCI-Express 1 PCIe 5.0 x16 LP slot(s)
<b>Integrated On board</b>	IPMI Support for Intelligent Platform Management Interface v.2.0, IPMI 2.0 with virtual media over LAN and KVM-over-LAN support LAN 1 RJ45 Dedicated BMC LAN port
<b>Add-on Options</b>	Raid Card None Optical Drive None
<b>Front Panel</b>	LED: HDD activity LED, Network activity LEDs, Power status LED, Universal Information (UID) LED Buttons: Power On/Off, UID button
<b>Drive Bays</b>	4x 2.5" hot-swap NVMe/SATA drive bays (4x 2.5" NVMe hybrid), M.2 : 2 M.2 NVMe OR 2 M.2 SATA3
<b>Power Supply</b>	Redundant 2200w Titanium Level(96%) High-Efficiency Power Supplies with I2C & PMBus
<b>Form Factor</b>	Form Factor 2U Rackmount Dimensions: Height - 3.46" (88mm), Width - 17.67" (449mm), Depth - 28" (711.2mm)
<b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b> <b>For more/current product information, visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b>	

AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries  
Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners