

Tyrone Camarero Specifications

Tyrone

Camarero: SSA200A2W-224

Key Feature

Virtualization , Software-defined Storage, AI Inference and Machine Learning, Cloud Computing, Enterprise Server

2U UP Hyper with 24 hot-swap 2.5" drive bays and 1 PCIe 5.0 slot

- 4th Generation AMD EPYC™ 9004 Series Processor, Single Socket SP5, Up to 128C/256T
- System on Chip
- 24 DIMM slots with 2 DIMM per channel (up to 6TB DDR5-4000MHz(1R)/3600MHz(2R)) OR
- 12 DIMM slots with 1 DIMM per channel (up to 3TB DDR5-4800MHz)"
- "Flexible networking options with 1 AIOM networking slot (OCP NIC 3.0 compatible)
- Configuration Options for up to;
- 4 PCIe 5.0 x16 Slots OR; 8 PCIe 5.0 x8 Slots or; 3 PCIe 5.0 x16 Slots + 2 PCIe 5.0 x8 Slots or; 2 PCIe 5.0 x16 Slots + 4 PCIe 5.0 x8 Slots or;
- 1 PCIe 5.0 x16 Slots + 6 PCIe 5.0 x8 Slots"
- 24 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bay(s)
- 2x 1600W Redundant Titanium Level (96%) power supplies
- 2 On-board NVMe M.2 slots; 1x PCIe 3.0 x4, 1x PCIe 3.0 x2; 80mm/110mm (Boot)



Processor/Cache		Front Panel	
Processor	4th Generation AMD EPYC™ 9004 Series Processor, Single Socket SP5, Up to 128C/256T	LED	HDD activity, LAN1 activity, Power status, System information
Chipset	System on Chip	Buttons	Power On/Off, UID button
System Memory		Drive bays	
Memory Capacity	24 DIMM slots with 2 DIMM per channel (up to 6TB DDR5-4000MHz(1R)/3600MHz(2R)) OR 12 DIMM slots with 1 DIMM per channel (up to 3TB DDR5-4800MHz)	HDD Bays	24 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bay(s)
Expansion Slot		Power Supply	
PCI-Express	Flexible networking options with 1 AIOM networking slot (OCP NIC 3.0 compatible) Configuration Options for up to; 4 PCIe 5.0 x16 Slots OR; 8 PCIe 5.0 x8 Slots or; 3 PCIe 5.0 x16 Slots + 2 PCIe 5.0 x8 Slots or; 2 PCIe 5.0 x16 Slots + 4 PCIe 5.0 x8 Slots or; 1 PCIe 5.0 x16 Slots + 6 PCIe 5.0 x8 Slots	Power Supply	
Integrated Onboard		Cooling System	
LAN	1 RJ45 1 GbE Dedicated IPMI LAN port(s)	4 counter-rotating 80x80x38mm Fan(s)	
Add-on Options		Form Factor	
Raid Card	Optional	Form Factor	
Optical Drive	None	2U Rackmount	
		Dimensions	
		Dimensions	
		Height :3.5" (88.9 mm), Width : 17.2" (437 mm), Depth : 29.9" (760 mm)	
		<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit</p> <p>www.tyronesystems.com</p>	

• AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries
 • Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks . All other brands and names are the property of their respective owners