

Tyrone Camarero Specifications

Tyrone

Camarero: SSA200C3A-11

Key Feature

1U UP Mainstream with up to 4 internal 2.5" SATA bays and 1 PCIe 5.0 slot
Web/Hosting Application, Email/Firewall/Application Server, Designed for small and medium businesses



- Single processor(s), AMD EPYC™ 4004 or AMD Ryzen™ 7000 / 9000 Series Processors, Supports 60W - 170W TDP CPUs (Air Cooled)
- 4x DDR5 UDIMM Slots, ECC/Non-ECC DDR5-5200 Up to total 192GB
- 1x PCIe 5.0 x16 (FHHL) slot
- IPMI 2.0 + KVM with Dedicated LAN (1GbE), 2x 1GbE LAN (Intel® I210-AT)
- 1 internal fixed 3.5" SATA drive bay,
Optional : 4 internal fixed 2.5" SATA* drive bays
- 2 M.2 PCIe 5.0 x4 NVMe slots (M-key 2280/22110)
- 6x 40mm Fan(s)
- 500W High-Efficiency Power Supply Platinum Level Certified

Processor/Cache	
Processor	Single processor(s), AMD EPYC™ 4004 or AMD Ryzen™ 7000 / 9000 Series Processors, Supports 60W - 170W TDP CPUs (Air Cooled)
Chipset	
Chipset	AMD B650
System Memory	
Memory Capacity	4x DDR5 UDIMM Slots, ECC/Non-ECC DDR5-5200 Up to total 192GB
Expansion Slot	
PCI-Express	1 PCIe 5.0 x16 FHHL slot
Integrated Onboard:	
SATA	4 SATA (6Gbps) port(s)
Network Connectivity	1 RJ45 1GbE with Realtek RTL8211F PHY (dedicated IPMI), 2 RJ45 1GbE with Intel® I210-AT
Add-on Options	
Raid Card	optional
Optical Drive	None

Front Panel	
LED	Fan Fail/System Over Heat LED, HDD activity LED, Network Activity LEDs, Power status LED
Buttons	Power On/Off button, System Reset button
Drive bays	
HDD Bays	1 internal fixed 3.5" SATA drive bay, Optional : 4 internal fixed 2.5" SATA* drive bays
Power Supply	
Power Supply	1x 500W Platinum Level (93%) power supply
Cooling System	
	6x 40mm Fan(s)
Form Factor	
Form Factor	1U Rackmount
Dimensions	
Dimensions	Height : 1.7" (43 mm), Width : 17.2" (437 mm), Depth : 16.9" (429 mm)
<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit</p> <p>www.tyronesystems.com</p>	