Tyrone Camarero Specifications

Camerero: SSA200F0R-48

Key Feature

- AMD EPYC™ 9004 series Processors, Single Socket SP5 supported, CPU TDP supports Up to 400W TDP
- System on Chip
- 12 DIMM slots, Up to 3TB 3DS ECC Registered RDIMM, DDR5-4800MHz
- 3 PCle 5.0 x16 (in x16 slot),2 PCle 5.0 x8
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 8 SATA3
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCle 4.0 x4 M.2 Form Factor: 2280, 22110
- Support 8 x 3.5"/2.5"(SATA)+2x 2.5"(SSD) Fix disks
- Cabinet with 3 x 2500 Mid Fan, 1 x Rear Fan
- 1200W Redundant Power Supply







Processor/Cache

AMD EPYC™ 9004 series Processors, Single **Processor**

Socket SP5 supported, CPU TDP supports

Up to 400W TDP

Chipset

Chipset System on Chip

System Memory

Memory Capacity 12 DIMM slots, Up to 3TB 3DS ECC Registered RDIMM, DDR5-4800MHz

Expansion Slot

3 PCle 5.0 x16 (in x16 slot), 2 PCle 5.0 x8

Integrated Onboard:

SATA 8 SATA3 (6Gbps) port(s)

Network Controllers Dual LAN with Broadcom BCM5720 1GBase-T

Add-on Options

Raid Card Optional

Optical Drive

None

Drive bays

Drive bays Support 8 x 3.5"/2.5"(SATA)+2x

2.5"(SSD) Fix disks

Power Supply

Power Supply 1200W Redundant Power Supply

Cooling System

Cabinet with 3 x 2500 Mid Fan, 1 x Rear Fan

Form Factor

4U Rackmount Form Factor

Email: Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners