

# Tyrone Camarero Specifications

# Tyrone

## Camarero SSA20C3R-54



### Key Feature

- "AMD Ryzen™ Threadripper™ PRO 7000 WX-Series and Ryzen™ Threadripper™ 7000 Series Processors
- AMD TRX50
- 4 DIMM slots, Up to 4TB ECC Registered RDIMM/3DS RDIMM, DDR5-5200MHz
- M.2 Interface: 2 PCIe 4.0 x4 (RAID 0, 1), M.2 Form Factor: 2280/22110, M.2 Key: M-Socket
- 2 PCIe 5.0 x16, support 2 triple/dual/single-width GPU cards, 2 PCIe 5.0 x8, open rear
- Dual 1Gb LAN with Broadcom BCM5720
- 4 SATA 3 (6Gb, RAID 0, 1, 10), 1 MCIO connector (PCIe Gen4 x8) to support 2 U.2 ports via cable for NVMe 2.5" SSD drives
- "1 USB 3.2 Gen2x2 (20G, 1 rear Type-C), 1 USB 3.2 Gen2x1 (10G, 1 header Type-C), 4 USB 3.2 Gen2x1 (4 rear Type-A) 1 USB 3.2 Gen1x1 (5Gb, 1 header Type-A 2 ports), 1 USB 2.0 (1 header Type-A 2 ports)"
- 1 Dedicated LAN for IPMI
- Overclocking supported on CPU and RDIMM
- 4x 3.5" Internal drive bay, 2x 2.5" drive bay
- 1x 12cm rear exhaust fan(s), 2x 12cm front cooling fan(s)
- 2000W PS2 Multi-output Power Supply

<b>Processor/Cache</b>		<b>Front Panel</b>	
<b>Processor</b>	"AMD Ryzen™ Threadripper™ PRO 7000 WX-Series and Ryzen™ Threadripper™ 7000 Series Processors Single socket sTR5, LGA-4844, Up to 350W TDP, Overclocking supported"	<b>LEDs</b>	Power status LED
<b>System Memory</b>		<b>Buttons</b>	Power On/Off button, LED light bar ON/OFF
<b>Memory</b>	"4 DIMM slots, Up to 4TB ECC Registered RDIMM/3DS RDIMM, DDR5-5200MHz"	<b>Port</b>	2x Audio Jacks, 1x USB 3.0 Gen 1-Type-c, 2x USB 3.0 Gen 1-Type-A, 2x USB 2.0
<b>Chipset</b>		<b>Drive bays</b>	
<b>Chipset</b>	AMD TRX50	<b>Drive Bays</b>	4x 3.5" Internal drive bay, 2x 2.5" drive bay
<b>Expansion Slot</b>		<b>Power Supply</b>	
<b>PCI-Express</b>	"2 PCIe 5.0 x8, Open rear, 2 PCIe 5.0 x16, metal armor protection, support 2 triple/ dual/ single-width GPU cards, 1 PCIe 4.0 x8, MCIO connector"	<b>Power Supply</b>	2000W PS2 Multi-output Power Supply
<b>Integrated On-Board</b>		<b>Cooling System</b>	
<b>SATA</b>	4 SATA3 ports; RAID 0,1,10	<b>Fans</b>	1x 12cm rear exhaust fan(s), 2x 12cm front cooling fan(s)
<b>Network Connectivity</b>	Single LAN with ASPEED AST2600, Dedicated LAN for IPMI, Dual LAN with 1Gb Broadcom BCM5720	<b>Form Factor</b>	
<b>Add-on Options</b>		<b>Form Factor</b>	5U Tower Dimensions: Height : 21.06" (535 mm), Width : 8.74" (222 mm), Depth : 22.56" (573 mm)
<b>Raid Card</b>	Optional	<b>Email : <a href="mailto:Info@tyronesystems.com">Info@tyronesystems.com</a></b>	
<b>Optical Drive</b>	None	<b>For more/current product information, Visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b>	

• Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other Countries  
 • Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners