Tyrone Camarero Specifications

Camarero SSA720TR-424RL

Key features

- Single AMD EPYC[™] 7003/7002 Series Processor, Socket SP3, Up to 64 Cores, System on Chip
- System on Chip

Ρ

C

S

Ε

In

- 2TB Registered ECC DDR4 3200MHz SDRAM in 8 DIMMs
- 5 PCI-E 4.0 x16 ,2 PCI-E 4.0 x8, M.2 Interface: 2 PCI-E 4.0 x4, M.2 Form Factor: 2280, 22110, M.2 Key: M-key
- 8 SATA3, 2 M.2, 8 SATA3 or 2 NVMe via single SlimSAS x8
- 2 Gigabit Ethernet LAN Ports
- ASPEED AST2500 BMC graphics
- Up to 6 USB 3.0 portS (4 rear + 2 via header)
- 7 PWM 4-pin Fans with tachometer status monitoring
- 24x 3.5" hot-swap SAS/SATA drive bays supporting SAS3/2 or SATA3 HDDs with 12Gbps throughput
- 2x 80mm rear hot-swap exhaust PWM fan(s), 3x 8cm hot-swap redundant PWM cooling fan(s)
- Redundant 1200W Titanium Level power supply

Processor/Cacl	10	Front Panel	
Processor	Single AMD EPYC [™] 7003/7002 Series Processor, Socket SP3, Up to 64 Cores, System on Chip	LEDs	Power status LED ,HDD activity LED, 2 Network Activity LEDs, Unit Identification (UID) LED, Fan Fail/System Over Heat LED
		Buttons	Power On/Off button;System Reset Button
Chipset		Drive Bays	
Chipset	System on Chip	HDD Bays	24x 3.5" hot-swap SAS/SATA drive bays supporting SAS3/2 or SATA3 HDDs with 12Gbps throughput
System Memor	У	Peripheral Driv	ves Optional 2x 2.5"" hot-swap drive bay, Optional 2x 2.5"" internal fixed drive bay, Optional 1x 3.5"" internal fixed drive bay
Memory Capacity	2TB Registered ECC DDR4 3200MHz SDRAM in 8 DIMMs	Power Supply	
		Redundant 1200W Titanium Level power supply	
Expansion Slot	S		
PCI-Express	5 PCI-E 4.0 x16, 2 PCI-E 4.0 x8, M.2 Interface: 2 PCI-E 4.0 x4, Form factor: 2280, 22110, Key: M-key	Cooling System 2x 80mm rear hot-swap exhaust PWM fan(s) , 3x 8cm hot-swap redundant PWM cooling fan(s)	
ntegrated Onboard		Form Factor	
•			
SATA	8 SATA3 (6 Gbps)	Form Factor	4U Rackmount
LAN	2 RJ45 Gigabit Ethernet LAN ports , 1 RJ45 Dedicated IPMI LAN port	Dimensions:	Height - 7" (178 mm), Width - 17.2" (437 mm), Depth - 26" (660 mm)
Add-on Opti	ons		,
Raid Card:	Optional	Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com	
Optical Drive:	Optional		

/rone







LEDS	Activity LEDs, Unit Identification (UID) LED, Fan Fail/System Over Heat LED			
Buttons	Power On/Off button;System Reset Button			
Drive Bays				
HDD Bays	24x 3.5" hot-swap SAS/SATA drive bays supporting SAS3/2 or SATA3 HDDs with 12Gbps throughput			
Peripheral Drive	es Optional 2x 2.5"" hot-swap drive bay, Optional 2x 2.5"" internal fixed drive bay, Optional 1x 3.5"" internal fixed drive bay			
Power Supply				
Redundant 1200W Titanium Level power supply				
Cooling System				
	ar hot-swap exhaust PWM fan(s) , swap redundant PWM cooling fan(s)			
Form Factor				
Form Factor	4U Rackmount			
Dimensions:	Height - 7" (178 mm), Width - 17.2" (437 mm),			

0 AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries

O Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners