

Tyrone Camarero Specifications

Camarero SSCOTI-34L

Key features

- **Entry-Level Workstation, Designed for CAD and 3D Modeling Applications, NVIDIA® Quadro® Professional GPU Support**
- Single Socket H4 (LGA 1151), CPU TDP support up to 95W Support Intel® Xeon® processor E-2100 / E-2200 series, 8th/9th Gen. Intel® Core™ i9/i7/i5/i3 Processors, Intel® Celeron®, Intel® Pentium® Up to 8-Cores"
- Intel® C246 chipset
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 2 PCI-E 3.0 x16 running at NA/16 or 8/8, 1 PCI-E 3.0 x4 slot, 1 PCI-E 3.0 x1 slot,
- 2 M.2 (M-key, 2260/2280/22110), 1 U.2 for optional expanded storages
- 2 USB Type A & Type C, 4 USB 3.1 Gen1 (2 rear + 2 front), 2 USB 2.0 (front)
- 1 HDMI 2.0a port, 1 DVI-Dport, 1 DP 1.2 port, 1 TPM header, 1 COM header
- 4 Fixed 3.5", Opt. 4 2.5" drive bays, 2 Standard 5.25" drive bays, 1 Fixed 3.5" device bay
- 668W Platinum Level Power Supply



Processor/Cache

Processor	Single Socket H4 (LGA 1151), CPU TDP support up to 95W Support Intel® Xeon® processor E-2100 / E-2200 series, 8th/9th Gen. Intel® Core™ i9/i7/i5/i3 Processors, Intel® Celeron®, Intel® Pentium® Up to 8-Cores
-----------	--

Chipset

Chipset	Intel® C246 chipset
---------	---------------------

System Memory

Memory Capacity	Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
-----------------	---

Expansion Slots

PCI Express	2 PCI-E 3.0 x16 running at NA/16 or 8/8, 1 PCI-E 3.0 x4 slot, 1 PCI-E 3.0 x1 slot,
-------------	--

Integrated On-Board

SATA	SATA3 (6Gbps) via Intel C246 controller, RAID 0, 1, 5, 10 support
------	---

LAN	2 RJ45 Ethernet LAN ports
-----	---------------------------

Add-on Options

Raid	Optional
Optical Drive	Optional

Front Panel

LED	Power LED, Hard drive activity LED, Network activity LED, System Information LED
-----	--

Buttons	Power On/Off button
---------	---------------------

Drive Bays

HDD Bays	4 Fixed 3.5", Opt. 4 2.5" drive bays, 2 Standard 5.25" drive bays, 1 Fixed 3.5" device bay
----------	--

Peripheral Bays	2 Standard 5.25" Peripheral drive bays, 1 Internal 3.5" Fixed device bay
-----------------	--

Power Supply

668W Platinum Level Power Supply

Cooling System

1x 12cm rear exhaust fan, Optional 1x 12cm front cooling fan

Form Factor

Form Factor	Mid-Tower
Height	16.7" (424mm),
Width	7.6" (193mm),
Depth	20.68" (525.3mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com