

Tyrone Camarero Specifications

Camarero- SSI100C3A-55

Key Feature

- 3rd Gen Intel® Xeon® Scalable processors, Intel® Xeon® W-3300 Processor, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Single LAN with Intel® Ethernet Controller I210-AT, Single LAN with Marvell AQC113, Single LAN with Realtek RTL8211F PHY (dedicated IPMI)
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz, Up to 4TB Intel® Optane™ Persistent Memory, DDR4-3200MHz, in 16 DIMM slots
- "4 PCI-E 4.0 x16, 3 PCI-E 4.0 x8 (in x16 slot),M.2 Interface: 4 PCI-E 4.0 x4, M.2 Form Factor: 2260/2280/22110, M.2 Key: M-Key M.2 support to RAID 0,1, 5, 10, VROC key is required for RAID."
- Intel® C621A controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port,VGA connector is dedicated for IPMI.
- HDD bays: External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- Front: 120 x 25 mm x1 PWM Fan,Rear: 120 x 25 mm x1 PWM Fan
- Power Supply : 550/1200W Redundant Platinum Power supply
Optional : 500/1200W Single Platinum Power Supply.



Processor/Cache		Front Panel	
Processor	3rd Gen Intel® Xeon® Scalable processors, Intel® Xeon® W-3300 Processor, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP	LED	Front Control Panel Power Switch, System Reset
System Memory		Buttons	Power On/Off button
Memory Capacity	Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz, Up to 4TB Intel® Optane™ Persistent Memory, DDR4-3200MHz, in 16 DIMM slots	Drive bays	
Chipset		HDD Bays	External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
Chipset	Intel® C621A	Power Supply	
Expansion Slot		Power Supply	550/1200W Redundant Platinum Power supply Optional : 500/1200W Single Platinum Power Supply
PCI-Express	4 PCI-E 4.0 x16, 3 PCI-E 4.0 x8 (in x16 slot),M.2 Interface: 4 PCI-E 4.0 x4, M.2 Form Factor: 2260/2280/22110, M.2 Key: M-Key M.2 support to RAID 0,1, 5, 10, VROC key is required for RAID.	Cooling System	
Integrated Onboard:		Fans	Front: 120 x 25 mm x1 PWM Fan,Rear: 120 x 25 mm x1 PWM Fan
SATA	Intel® C621A controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10	Form Factor	
LAN	1 RJ45 Dedicated IPMI LAN port, 1 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 10GBase-T ports	Form Factor	Tower/5U Rackmount
Raid Card	Optional	Dimensions	
Optical Drive	None	Dimensions	"Dimensions: 560 x 200 x 430 mm (22" x 7.9" x 16.9") "
		<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit</p> <p>www.tyronesystems.com</p>	