

Tyrone Camarero Specifications

Tyrone®

Camarero SSI100C3S-445H

Key features

- Database Applications Backup Storage, Cold Storage Data Warehousing, Archiving
- Single Socket P+ (LGA 4189), Support Intel® 3rd Gen Xeon® Scalable Processors, Support CPU TDP 270W
- Intel® C621A chipset
- 8 DIMMs; Supports 3DS DDR4-3200: RDIMM/LRDIMM/Intel® DCPMM
- 2 PCI-E 4.0 x16 (LP) slots, 2 PCI-E 4.0 x8 (LP) slots
- Intel® Ethernet Controller X550 2x 10GbE RJ45
- 45x 3.5" hot-swap SATA/SAS drive bays
- 5x (8cm x8cm x3.8cm) heavy duty fans with optimal fan speed control
- Redundant Platinum 1600W Power Supply



Processor/Cache		Front Panel	
Processor	Single Socket P+ (LGA 4189), Support Intel® 3rd Gen Xeon® Scalable Processors, Support CPU TDP 270W	LEDs	Device Activity, LAN 1 Activity, LAN 2 Activity, Power Failure LED, Power status, System information
Chipset	Intel® C621A chipset	Buttons	Power On/Off button, System Reset
System Memory		Drive Bays	
Memory Capacity	8 DIMMs; Supports 3DS DDR4-3200: RDIMM/LRDIMM/Intel® DCPMM	HDD Bays	45x 3.5" hot-swap SATA/SAS drive bays
Expansion Slots		Power Supply	
PCI-Express	2 PCI-E 4.0 x16 (LP) slots, 2 PCI-E 4.0 x8 (LP) slots	Redundant Platinum 1600W Power Supply	
Integrated Onboard		Cooling System	
SATA	SATA3 (6Gbps) via C621A Chipset; RAID 0, 1, 5, 10 support	5x (8cm x8cm x3.8cm) heavy duty fans with optimal fan speed control	
SAS	SAS3 (12Gbps) via Broadcom 3908; RAID 0, 1, 5, 6, 10, 50, 60 support	Form Factor	
Network Connectivity	2x 10GbE BaseT with Intel® X550	Form Factor	4U Rackmount
Add-on Options		Dimensions:	Height : 7" (178mm), Width : 17.2" (437mm), Depth : 26" (660mm)
Optical Drive	Optional	Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com	