

Tyrone Camarero Specifications

Camarero- SSI10C3R-28 Key Feature



- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP6 Phase Power Design
- Intel® C621A
- Up to 2TB RDIMM, DDR4-3200MHz; Up to 2TB LRDIMM, DDR4-3200MHz, Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 2 PCIe 4.0 x16, 2 PCIe 4.0 x8, 1 PCIe 4.0 x8 (in x16 slot), 1 PCIe 4.0 NVMe x8 Internal Port(s), M.2 Interface: 1 SATA/PCIe 3.0 x4 M.2 Form Factor: 2280/22110, M.2 Key: M-Key
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 8x 3.5"(tool-less) or 2.5"(screw) hot-swap SAS3/SATA drive bay, Optional 2x 3.5" fixed drive bay, Optional rear 2x 2.5" hot-swap drive bay kit
- 3x 80mm heavy duty fan(s) with PWM fan(s) speed control
- Dual LAN with 10GBase-T with Intel® X550
- 600W / 650W 1U Redundant Power Supply

Processor/Cache	
Processor	3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
System Memory	
Memory Capacity	8 DIMM slots, Up to 2TB Intel® Optane™ Persistent Memory 200 Series, Up to 2TB ECC LRDIMM, DDR4-3200MHz; Up to 2TB ECC RDIMM, DDR4-3200MHz
Chipset	
Chipset	Intel® C621A
Expansion Slot	
Expansion Slot	2 PCIe 4.0 x16, 1 PCIe 4.0 x8 (in x16 slot), 2 PCIe 4.0 x8, M.2 Interface: 1 SATA/PCIe 3.0 x4, Form Factor: 2280/22110, Key: M-Key
Integrated Onboard:	
SATA	Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN	2 RJ45 10 Gigabit Ethernet LAN ports
IPMI	ASPEED AST2600 BMC
Add-on Options	
Raid Card	None
Optical Drive	Optional

Front Panel	
LEDs	Power status LED, HDD activity LED, System Information LED, Power Fail LED, 2 Network Activity LEDs
Buttons	PowerPower On/Off button, System
Drive bays	
HDD Bays	Optional 2x 2.5" hot-swap SAS3/SATA drive bay, Optional 2x 3.5" fixed drive bay, 8x 3.5" (tool-less) or 2.5" (screw) hot-swap SAS3/SATA drive bay
Peripheral Drives	Optional 1x slim DVD-ROM drive bay, Optional 1x COM port tray, Optional 2x USB 2.0 ports, Optional 2x USB 3.0 ports
Power Supply	
Power Supply	600W / 650W 1U Redundant Power Supply
Cooling System	
Fans	3x 80mm heavy duty fan(s) with PWM fan(s) speed control
Form Factor	
Form Factor	2U Rackmount
Dimensions	
Dimensions	Height - 3.5" (89 mm), Width -17.2" (437 mm), Depth -25.5" (647 mm)
<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit</p> <p>www.tyronesystems.com</p>	