

Tyrone Camarero Specifications



Camarero SSI10E3R-12

Key features

General Purpose, Front-end, Web Hosting, Entry Appliance

- Single Socket H5 LGA 1200, Support Intel® Xeon® processor E-2300 series and 10th Gen. Pentium® Processors Support CPU TDP 95W
- Intel® C252
- 4 DIMMs; Up to 128GB of DDR4 ECC UDIMM memory with speeds of up to 3200MHz
- 1 PCI-E 4.0 x8 (in x16 FHHL)
- Intel® Ethernet Controller i210 2x 1GbE RJ45
- 1 Fixed 3.5" drive support (default); Up to 2 Fixed 3.5" drives or 3 Fixed 2.5" drives (opt.); Onboard 1x NVMe M.2
- 2 counter-rotation PWM 40x40x56mm Fan(s)
- Single Platinum 350W Power Supply



Processor/Cache		Front Panel	
Processor	Single Socket H5 LGA 1200, Support Intel® Xeon® processor E-2300 series and 10th Gen. Pentium® Processors Support CPU TDP 95W	LEDs	Device Activity LAN 1 Activity ,LAN 2 Activity, Power status,System information
Chipset	Intel® C252	Buttons	Power On/Off,System Reset
System Memory		Drive Bays	
Memory Capacity	4 DIMMs; Up to 128GB of DDR4 ECC UDIMM memory with speeds of up to 3200MHz	HDD Bays	1 Fixed 3.5" drive support (default); Up to 2 Fixed 3.5" drives or 3 Fixed 2.5" drives (opt.); Onboard 1x NVMe M.2
Expansion Slots		Power Supply	
PCI-Express	1 PCI-E 4.0 x8 (in x16 FHHL)	Single Platinum 350W Power Supply	
Integrated Onboard		Cooling System	
SATA	SATA3 (6Gbps); RAID 0/1/5/10 support	2 counter-rotation PWM 40x40x56mm Fan(s)	
LAN	1 RJ45 Dedicated IPMI LAN port , 2 RJ45 1GbE LAN ports	Form Factor	
Add-on Options		Form Factor	1U Rackmount
Raid Card	Optional	Dimensions:	Height : 1.7" (43mm), Width :17.2" (437mm), Depth : 14.5" (368mm)
Optical Drive	None	Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com	