

Tyrone Camarero Specifications

Tyrone

Camarero: SSI10E3R-34.ai

Key Feature

Entry-Level System for SOHO and SMB, Storage, application and centralized data backup system Applications, IPMI for remote management



- Single Socket H5 (LGA-1200), Intel® Xeon® processor E-2300 series and 10th Gen. Pentium® Processors
- PCIe 4.0 Support
- Dual LAN ports, GbE and dedicated IPMI LAN port
- 9cm PWM quiet exhaust fan and optional front intake fan
- 400W 80PLUS Gold Power Supply
- 4 internal fixed 3.5" SATA drive bay(s)

Processor/Cache		Front Panel	
Processor	Single Socket H5 (LGA-1200), Intel® Xeon® processor E-2300 series and 10th Gen. Pentium® Processors	LED	HDD activity LED, Network activity LEDs, Power LED, System Overheat LED
Chipset		Buttons	Power On/Off button
Chipset	Intel® C252	Drive bays	
System Memory		HDD Bays	4 internal fixed 3.5" SATA drive bay(s), M.2 : 1 M.2 PCIe 3.0 x4 NVMe slot(s) (M-key 2280/22110)
Memory Capacity	4 DIMM slotsMax Memory (2DPC): Up to 128GB 3200MT/s ECC DDR4 UDIMM	Peripheral Bays	2 5.25" bay(s)
Expansion Slot		Power Supply	
PCI-Express	2 PCIe 4.0 x8 FHFL slot(s), 1 PCIe 4.0 x4 FHFL slot(s), 1 PCIe 3.0 x2 FHFL slot(s)	Power Supply	1x 400W Gold Level (90%) power supply
Integrated Onboard		Cooling System	
SATA	SATA (6Gbps)	1x 90mm Fan(s)	
Network Connectivity	2 RJ45 1GbE with Intel® I210-AT	Form Factor	
Add-on Options		Form Factor	
Raid Card	Optional	3U Rackmount	
Optical Drive	Optional	Dimensions	
		Dimensions	
		Height :14.25" (362 mm), Width : 7.25" (184 mm), Depth : 16.75" (425 mm)	
		<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit</p> <p>www.tyronesystems.com</p>	