

Tyrone Camarero Specifications

Tyrone

Camarero- SSI200A2W-212

Key Feature

2U UP CloudDC with 12 hot-swap 3.5" SAS/SATA (2 NVMe hybrid) bays and 6 PCIe 5.0 slots + 1 PCIe 5.0 AIOM slot
 Cloud Computing, Data Center Optimized, Network Appliance, AI inferencing, ML training, Database/Storage



- Single Socket E (LGA-4677) 4th/5th Gen Intel® Xeon® Scalable processors. Up to 350W TDP
- Intel C741 Chipset
- 16 DIMMs; Supports 3DS DDR5 RDIMM. Up to 5600 MHz
- 4 PCIe 5.0 x8 FHFL slot(s), 2 PCIe 5.0 x16 FHHL slot(s), 1 PCIe 5.0 x16 AIOM slot(s) (OCP 3.0 compatible)
- Single AIOM with NCSI (OCP 3.0) for networking, 1 dedicated IPMI LAN
- 12x front hot-swap 3.5" SATA3 drive bays (Optional 2 hybrid Gen5 NVMe), SAS3 with additional SAS controller card
- Fans : 3 heavy duty PWM 80x80x38mm Fan(s)
- 2x 1200W Redundant (1 + 1) Titanium Levelpower supplies

Processor/Cache	
Processor	Single Socket E (LGA-4677) 5th Gen Intel® Xeon®/ 4th Gen Intel® Xeon® Scalable processors, Up to 64C/128T; Up to 320MB Cache Note : Supports up to 350W TDP CPUs (Air Cooled)
System Memory	
Memory Capacity	16 DIMMs; Supports 3DS DDR5 RDIMM. Up to 5600 MHz
Chipset	
Chipset	Intel® C741 Chipset
Expansion Slot	
Expansion Slot	4 PCIe 5.0 x8 FHFL slot(s), 2 PCIe 5.0 x16 FHHL slot(s), 1 PCIe 5.0 x16 AIOM slot(s) (OCP 3.0 compatible)
Integrated Onboard:	
LAN	1 RJ45 Dedicated IPMI LAN port
SATA	SATA (6Gbps) ; RAID 0/1/5/10 support
Add-on Options	
Raid Card	Optional
Optical Drive	None

Front Panel	
LED	Drive activity, Network activity, Power status Universal Information (UID)
Buttons	Power On/Off Universal Information
Drive bays	
HDD Bays	12x 3.5" NVMe/SATA/SAS drive bays (2x 3.5" NVMe hybrid) 2x PCIe 3.0 x 2 M-key, 2280, 22110
Power Supply	
Power Supply	2x 1200W Redundant (1 + 1) Titanium Levelpower supplies
Cooling System	
Fans	3 heavy duty PWM 80x80x38mm Fan(s)
Form Factor	
Form Factor	2U Rackmount
Dimensions	
Dimensions	Height 3.5" (89mm), Width 17.2" (437mm), Depth 25.5" (648mm)
<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit www.tyronesystems.com</p>	

• Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries
 • Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners