

Tyrone Camarero Specifications

Tyrone

Camarero: SSI200C3R-34

Key Feature

UP mid tower with 4 internal 3.5" SATA drive bays and PCIe 5.0 Storage, application and centralized data backup system ApplicationsIPMI for remote managementEntry-Level Server for SOHO and SMB



- Supports Intel® Xeon® E-2400 Series Processors
- PCIe 5.0 Support
- Dual LAN ports, GbE and dedicated IPMI LAN port
- 9cm PWM quiet exhaust fan and optional front intake fan
- 400W 80PLUS Gold Power Supply

Processor/Cache		Front Panel	
Processor	"Single processor(s) Intel® Xeon® E-2400 series Processors and 12th Gen. Pentium® Processors"	LED	HDD activity LED, Network activity LEDs, Power LED, System Overheat LED
Chipset		Buttons	Power On/Off button
Chipset	Intel® C262	Drive bays	
System Memory		HDD Bays	4 internal fixed 3.5" SATA drive bay(s)
Memory Capacity	4 DIMM slots Max Memory (2DPC): Up to 128GB 4400MT/s ECC DDR5 UDIMM	Peripheral Bays	2 5.25" bay(s)
Expansion Slot		Power Supply	
PCI-Express	2 PCIe 5.0 x8 FHFL slot(s), 1 PCIe 4.0 x4 FHFL slot(s), 1 PCIe 4.0 x4 FHHL slot(s)	Power Supply	1x 400W Gold Level (90%) power supply
Integrated Onboard		Cooling System	
SATA	SATA (6Gbps) ; RAID 0/1/5/10 support		1x 90mm Fan(s)
Network Connectivity	1 RJ45 1GbE with Realtek RTL8211F PHY (dedicated IPMI), 2 RJ45 1GbE with Intel® I210	Form Factor	
Add-on Options		Form Factor	3U Rackmount
Raid Card	Optional	Dimensions	
Optical Drive	None	Dimensions	Height :14.25" (362 mm), Width : 7.25" (184 mm), Depth : 16.75" (425 mm)
		<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit</p> <p>www.tyronesystems.com</p>	