

Tyrone Camarero Specifications

Tyrone

Camarero- SSI200F0A-54

Key Feature

Product Design and Engineering Simulation.

- Socket E (LGA4677) support Intel® Xeon® W-3400 processors
- Intel® W790
- 16 DIMMs
- 1x 1GbBaseT, 1x 10GbBaseT
- 2 2.5" SATA3 drive bays; 4 3.5" SATA3 drive bays; ; 4 M.2 NVMe
- 1 120 mm Fan(s) ; 2 120 mm Fan(s)
- 500W/1200W/2000W Single Power Supplies 80Plus Platinum Level, Optional : 550/1200W Redundant Power Supply 80Plus Platinum
- Supported GPU
NVIDIA PCIe: T1000, RTX A6000, RTX A5000, RTX A5500, RTX A4000, RTX A2000, RTX 6000 ADA
- Max GPU Support Count
Up to 2 Triple-width or 4 Double-width or 4 Single-width GPU(s)



Processor/Cache		Drive bays	
Processor	Single Socket E (LGA4677) Intel® Xeon® W-3400 processors.	HDD Bays	4x 3.5" SATA drive bays
System Memory		M.2	4 M.2 PCIe 5.0 x4 NVMe slot(s)
Memory Capacity	16 DIMM slots Up to 4TB: 16x 256 GB DRAM Memory Type: 4800MHz ECC DDR5 RDIMM / LRDIMM	Peripheral Bays	2x 5.25" drive bays
Chipset		Optical Drive	Optional (In Peripheral Bays)
Chipset	Intel W790	Power Supply	
Expansion Slot		Power Supply	500W/1200W/2000W Single Power Supplies 80Plus Platinum Level, Optional : 550/1200W Redundant Power Supply 80Plus Platinum
PCI-Express	6 PCIe 5.0 x16 slot(s)	Cooling System	
Integrated Onboard:		Fans	1x 120mm Fan(s), 1x 120mm Fan(s) (optional) , 1x 120mm Fan(s) (optional), 2x 120mm Fan(s)
IPMI	Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support	USB	2 USB 2.0 port(s) (rear), 2 USB 2.0 Type-A port(s) (front), 2 Type-A port(s) (Front),1 VGA port(s)
Network Connectivity	1x 10GbE BaseT with Marvell AQC113 1x 1GbE BaseT with Intel® I210-AT	Form Factor	
Front Panel		Form Factor	Tower or 5U Rackmount
LED	Power status LED	Dimensions	
Buttons	LED On/Off Button Power On/Off button	Dimensions	(W x H x L) 150 x 86 x 200 mm
		<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit www.tyronesystems.com</p>	

• Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other Countries
 • Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners