

Tyrone Camarero Specifications

Tyrone

Camarero: SSI20C3R-14

Key Feature

1U Mainstream server with 8 hot-swap 3.5" SAS/SATA bays, 2 PCIe 5.0 slots and internal SAS slot

Web/Hosting Application, Email/Firewall/Print Server, General Purpose



- Single Socket V0 (LGA-1700) supports Intel® Xeon® E-2400 series, Intel® Pentium® processors
- Intel® C266
- 4 DIMMs; Up to 128GB of DDR5 ECC UDIMM memory with speeds of up to 4400MHz
- 1 PCIe 5.0 x16 or 2 PCIe 5.0 x8 (FHHL & LP); 1 Dedicated Internal HBA slot
- Intel® Ethernet Controller i210 2x 1GbE RJ45
- 4 front hot-swap 3.5" SAS*/SATA drive bay(s)
- Default single Titanium 600W Power Supply; Optional redundant power by adding 1x Power Supply Module



Processor/Cache		Front Panel	
Processor	Single Socket V0 (LGA-1700) supports Intel® Xeon® E-2400 series, Intel® Pentium® processors	LED	Device Activity, LAN 1 Activity, LAN 2 Activity, Power status System information
Chipset		Buttons	Power On/Off System Reset UID button.
Chipset	Intel® C266	Drive bays	
System Memory			4 front hot-swap 3.5" SAS*/SATA drive bay(s)
Memory Capacity	Slot Count: 4 DIMM slots/2 Channels, Max Memory (2DPC): Up to 128GB 4400MT/s ECC DDR5 UDIMM	Power Supply	
Expansion Slot		Power Supply	Default single Titanium 600W Power Supply; Optional redundant power by adding 1x Power Supply Module
PCI-Express	"1 PCIe 5.0 x8 FHHL slot(s), 1 PCIe 5.0 x8 LP slot(s) Option A, 1 PCIe 5.0 x16 FHHL slot(s)"	Cooling System	
Integrated Onboard:			2 AOC cooling Fan(s) (optional), 4 middle cooling PWM 40x40x28mm Fan(s)
SATA	SATA (6Gbps) ; RAID 0/1/5/10 support	Form Factor	
LAN	2 RJ45 1 GbE LAN port(s), 1 RJ45 1 GbE Dedicated IPMI LAN port(s) (IPMI shared on LAN port 1)	Form Factor	1U Rackmount
Add-on Options		Dimensions	
Raid Card	Optional	Dimensions	Height 1.7" (43mm), Width 17.2" (437mm), Depth 19.98" (507 mm)
Optical Drive	None	<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit</p> <p>www.tyronesystems.com</p>	