Tyrone Camarero Specifications

Tyrone®

Camarero SSi00TR-32

Key features

- Single socket H4 (LGA 1151) supports Intel® 7th/6th Gen. Core™ i7/i5/i3 series
- Intel®B250 Express Chipset
- Up to 64GB Non-ECC UDIMM, DDR4-2400MHz, in 4 DIMM slots
- 1 GbE LAN port via Intel® i219V
- 6 SATA3 (6Gbps)
- 1 PCI-E 3.0 x16, 1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1
- 1 PCIe 3.0 x4 M.2 (2280 form factor)
- 6 USB 3.0 (4 rear, 2 via header) 4 USB 2.0 (2 rear, 2 via headers)
- 1 DP (Display Port), 1 HDMI, 1 DVI-D
- HD Audio 7.1 channel connector by Realtek ALC888S, support SPDIF-Out
- Rich Front I/O: 2 USB 3.0, 2 USB 2.0, Headphone jacks
- Security: Chassis Intrusion sensor and Kensington Lock Support
- Easy Access: Tool-less side panel, PCI-E card, and HDD installations.
- 2 x 5.25" drive bay,2 x 3.5" fixed drive bay,1 x 2.5" fixed drive bay
- 1 x 80mm Rear fan(s)
- PS2/ATX 260W/300W Multi-output power supply 80Plus Bronze, with 24pin Cable

intel inside™ **XEON**®

Processor/Cache

Processor	Single socket H4 (LGA 1151) supports Intel® 7th/6th Gen. Core™ i7/i5/i3 series

Chipset

Chipset	Intel®B250 Express Chipset

System Memory

Memory Capacity	4x 288-pin DDR4 DIMM slots, Supports up to 64GB DDR4 Non-ECC Un-Buffered memory (UDIMM) in 4 DIMM slots

Expansion Slots

PCI-Express	1 PCI-E 3.0 x16, 1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1

Integrated On-Board

SATA	SATA3 via PCH
LAN	1 RJ45 Gigabit Ethernet LAN port

Add-on Options

Raid Card	Optional
Optical Drive	Optional

Front Panel

LED Indicators	1 Network Activity LEDs, HDD activity LED, Power LED
Buttons	Power On/Off button

Drive Bays

HDD Bays	2 x 5.25" drive bay,2 x 3.5" fixed drive bay,1 x 2.5" fixed drive bay

Power Supply

PS2/ATX 260W/300W Multi-output power supply 80Plus Bronze, with 24pin Cable

Cooling System

1 x 80mm Rear fan(s)

Form Factor

Form Factor		Mini-tower
Height	:	14.65" (372 mm),
Width	:	6.89" (175 mm),
Depth	:	16.85" (428 mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com