

Tyrone Camarero Specifications

Tyrone®

Camarero SSi00TR-34L

Key features

- Intel® 6th Generation Core™ i3 series, Intel® 6th Generation Core™ i5 series, Intel® 6th Generation Core™ i7 series, Intel® 7th Generation Core™ i3 series, Intel® 7th Generation Core™ i5 series, Intel® 7th Generation Core™ i7 series, Single Socket H4 (LGA 1151) supported; CPU TDP support Up to 120W TDP
- Intel® Z270 Express
- Up to 64GB Unbuffered non-ECC UDIMM, DDR4-2800MHz (O.C), in 4 DIMM slots
- 2 PCI-E 3.0 x16 slots (16/NA or 8/8). 1 PCI-E 3.0 x4, 3 PCI-E 3.0 x1 M.2 Interface: PCIe 3.0 x4 and PCIe 3.0 x4. M.2 Form Factor: 22110, 22110 (RAID 0,1 support)
- 1 HDMI port(s), 1 DP (DisplayPort) port(s), 1 DVI - D port(s)
- Intel® Z270 Express controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single Intel® single Ethernet PHY i219V
- 4 x 3.5" fixed drive bay. Optional 4 x 2.5" fixed drive bay
- 1 x 12cm rear exhaust fan(s). Optional 1 x 12cm (front) cooling fan
- 900W Gold Level Certified High-Efficiency Power Supply



Processor/Cache

Processor	Intel® 6th Generation Core™ i3 series, Intel® 6th Generation Core™ i5 series, Intel® 6th Generation Core™ i7 series, Intel® 7th Generation Core™ i3 series, Intel® 7th Generation Core™ i5 series, Intel® 7th Generation Core™ i7 series, Single Socket H4 (LGA 1151) supported; CPU TDP support Up to 120W TDP
-----------	---

Chipset

Chipset	Intel® Z270 Express
---------	---------------------

System Memory

Memory Capacity	Up to 64GB Unbuffered non-ECC UDIMM, DDR4-2800MHz (O.C), in 4 DIMM slots
-----------------	--

Expansion Slots

PCI-Express	2 PCI-E 3.0 x16 slots (16/NA or 8/8). 1 PCI-E 3.0 x4, 3 PCI-E 3.0 x1. M.2 Interface: PCIe 3.0 x4 and PCIe 3.0 x4. M.2 Form Factor: 22110, 22110 (RAID 0,1 support)
-------------	--

Integrated On-Board

SATA	Intel® Z270 Express controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN	Single Intel® single Ethernet PHY i219V

Add-on Options

Raid Card	Optional
Optical Drive	Optional

Front Panel

LED Indicators	1 Network Activity LEDs, HDD activity LED, Power Status LED, System Overheat LED
Buttons	Power On/Off button

Drive Bays

HDD Bays	4 x 3.5" fixed drive bay. Optional 4 x 2.5" fixed drive bay
Peripheral Bays	2 x standard 5.25" drive bay, 1 x 3.5" internal fixed drive bay

Power Supply

900W Gold Level Certified High-Efficiency Power Supply
--

Cooling System

1 x 12cm rear exhaust fan(s). Optional 1 x 12cm (front) cooling fan

Form Factor

Form Factor	Mid-tower
Height	: 16.7"(424 mm),
Width	: 7.6"(193 mm),
Depth	: 20.68"(525 mm)

Email : info@tyronesystems.com

**For more/current product information, visit
www.tyronesystems.com**