

Tyrone Camarero Specifications

Tyrone[®]

Camarero SSiOTD-34L

Key features



Gaming, Digital Imaging, Entry-Level Workstation, Simulation and Creation Design

- Single socket H4 (LGA 1151) supports Intel® 7th/6th Gen. Core™ i7/i5/i3 series
- Intel® Z270 Express Chipset
- Up to 64GB Non-ECC UDIMM DDR4-3733MHz (OC), in 4 DIMM slots
- 4 PCI-E 3.0 x16 (run at 16/NA/16/NA, 8/8/8/8, Auto Switch), 1 PCI-E 3.0 x4
- 2 PCIe 3.0 x4 M.2 (support 22110) 1 compatible w/ SATA; RAID 0, 1 support
- 2 PCIe 3.0 x4 U.2 (1 share with M.2); RAID 0, 1 support
- USB 3.1/3.0/2.0, 2 GbE LAN ports (1 via Intel i210-AT, 1 via Intel i219V)
- Removable 3.5" and 2.5" HDD/SSD cages with tool-less trays for up to 10 drives; 2x 5.25" Peripheral Drive Bays
- 1 DP (Display Port), 1 HDMI
- HD Audio 7.1 channel connector by Realtek ALC1150, support SPDIF-Out
- 750W Multi-output ATX Power Supply with modular cable; 80Plus Gold

Processor/Cache

Processor	Single socket H4 (LGA 1151) supports Intel® 7th/6th Gen. Core™ i7/i5/i3 series
-----------	--------------------------------------------------------------------------------

Chipset

Chipset	Intel® Z270 Express Chipset
---------	-----------------------------

System Memory

Memory Capacity	4x 288-pin DDR4 DIMM slots, Supports up to 64GB DDR4 Non-ECC Un-Buffered memory (UDIMM) in 4 DIMM slots
-----------------	---------------------------------------------------------------------------------------------------------

Expansion Slots

PCI-Express	4 PCI-E 3.0 x16 (run at 16/NA/16/NA, 8/8/8/8, Auto Switch), 1 PCI-E 3.0 x4
-------------	----------------------------------------------------------------------------

Integrated On-Board

SATA	SATA3 via PCH w/ RAID 0, 1, 5, 10
LAN	2 RJ45 Gigabit Ethernet LAN ports

Add-on Options

Raid Card	Optional
Optical Drive	Optional

Front Panel

LED Indicators	Power LED, Hard drive activity LED
Buttons	Power On/Off button, Reset Button

Drive Bays

HDD Bays	4x 2.5" drive bays, and 6x combination bays that can house either 3.5" or 2.5" drives
Peripheral Drives	2x 5.25" Peripheral Drive Bays

Power Supply

750W Multi-output ATX Power Supply with modular cable; 80Plus Gold

Cooling System

3x 12cm PWM fans, Compatible with 120mm and 240mm closed-loop water cooling kits

Form Factor

Form Factor	Mid-Tower
Height	: 18.1" (460mm),
Width	: 7.9" (201mm),
Depth	: 19.4" (493mm)

Email : info@tyronesystems.com

**For more/current product information, visit
www.tyronesystems.com**