

## Tyrone Camarero Specifications

### Camarero- TDI100C3R-212.

#### Key Feature

- Dual Socket P+ (LGA-4189), 3rd Gen Intel® Xeon® Scalable processors
- Intel® C621A chipset
- 16 DIMM slots , Max 4TB memory
- 2 PCI-E 4.0 x16 and 4 PCI-E 4.0 x8
- 12x 3.5/2.5" SATA drive bays , SAS3 with additional SAS controller card
- 1200W/1600W Redundant Power supply



Processor/Cache	
<b>Processor</b>	Dual Socket P+ (LGA-4189), 3rd Gen Intel® Xeon® Scalable processors
System Memory	
<b>Memory Capacity</b>	16 DIMM slots , Max 4TB memory
Chipset	
<b>Chipset</b>	Intel® C621A chipset
Expansion Slot	
<b>Expansion Slot</b>	2 PCI-E 4.0 x16 and 4 PCI-E 4.0 x8
Integrated Onboard	
<b>SATA</b>	SATA3 (6Gbps)
<b>Network Connectivity</b>	1GbE port, 1 Dedicated IPMI LAN port

Drive bays	
<b>HDD Bays</b>	12x 3.5/2.5" SATA drive bays , SAS3 with additional SAS controller card
Power Supply	
<b>Power Supply</b>	1200W/1600W Redundant Power supply
Cooling System	
<b>Fans</b>	3 Cooling fans
Form Factor	
<b>Form Factor</b>	2U Rackmount
<p><b>Email : <a href="mailto:Info@tyronesystems.com">Info@tyronesystems.com</a></b></p> <p><b>For more/current product information, Visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	