

Tyrone Camarero Specifications

Tyrone

Camarero: TDI100F0R-48

Key Feature

Dual Socket Intel Ice Lake SP CPU, 3rd Gen Intel Xeon Scalable Processor, LGA4189

- (8)+(8) DIMM slots DDR4 ECC RDIMM/RDIMM 3DS/LRDIMM/LRDIMM 3DS 3200, Up to 2,048GB RDIMM/ 4,096GB LRDIMM/ 4,096GB RDIMM 3DS/LRDIMM 3DS *Follow latest Intel DDR4 Memory POR
- Intel C621A chipset
- 3 PCIe Gen. 4x16 + 2 PCIe Gen.4x8 slots
- 2 PCIe x8 SlimSASconnectors (NVMe)
- 2 NVMe 22110 / 2280 M.2 slots
- 2 1000Base-T LAN + 1 dedicate 1000Base-T IPMI ports
- AST2600 BMC with IPMI 2.0 & Redfish support
- Support 8 x 3.5"/2.5"(SATA)+2x 2.5"(SSD) Fix disks
- Support Single width 4 GPUs and Dual Width 2GPUs
- Cabinet with 3 x 2500 Mid Fan, 1 x Rear Fan
- FSP 1200W Single/Redundant Power Supply



Processor/Cache		Drive bays	
Processor	Dual Socket Intel Ice Lake SP CPU, 3rd Gen Intel Xeon Scalable Processor, LGA4189	Drive bays	Support 8 x 3.5"/2.5"(SATA) +2x 2.5"(SSD) Fix disks
System Memory		Power Supply	
Memory Capacity	(8)+(8) DIMM slots DDR4 ECC RDIMM/RDIMM 3DS/LRDIMM/LRDIMM 3DS 3200, Up to 2,048GB RDIMM/ 4,096GB LRDIMM/ 4,096GB RDIMM 3DS/LRDIMM 3DS	Power Supply	FSP 1200W Single/Redundant Power Supply
Chipset		Cooling System	
Chipset	Intel C621A chipset	Cooling System	Cabinet with 3 x 2500 Mid Fan, 1 x Rear Fan
Expansion Slot		Form Factor	
PCI-Express	3 PCIe Gen. 4x16 + 2 PCIe Gen.4x8 slots	Form Factor	4U Rackmount
Integrated Onboard:		<p style="text-align: center;">Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com</p>	
SATA	(3) Mini-SAS HD from PCH SATA-III		
LAN	Intel I210-AT		
IPMI	IPMI 2.0 compliant baseboard management controller (BMC) / 10/100/1000 Mb/s MAC interface		
Add-on Options			
Raid card	Optional		
Optical Drive	Optional		