

Tyrone Camarero Specifications

Tyrone

Camarero AD400TE1-212R

Key features

- EATX Server Board with dual Xeon Scalable processors
- Intel C621
- DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)
- 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards
- LAN1: Intel I210AT , LAN2: Intel I210AT, 10/100/1000 Mbps, 2 x RJ-45
- 10 SATA3 and six USB3.0 ports
- One M.2 2280 (SATA / PCIe compatible)
- 0 ~ 40 °C ambient operation temperature range
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES3, optional 2 x 2.5" hot-swap drive bay
- 3 x 8cm high-performance PWM fan(s),Optional 5 x 6cm 4pin high performance fan(s)
- 920W Redundant Platinum Super Quiet power supply W/PMbus



Processor/Cache

Processor EATX Server Board with dual Xeon Scalable processors

Chipset

Chipset Intel C621

System Memory

Memory Capacity DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)

Expansion Slots

PCI-Express 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards

Integrated On-Board

SATA 10 x SATAIII (RAID 0,1,5,10)

LAN Intel I210AT; LAN2: Intel I210AT

Add-on Options

Raid Card Optional

Optical Drive None

Front Panel

Led's 2 Network Activity LEDs,Fan Fail/System Over Heat LED,HDD activity LED,Power Status LED, Unit Identification (UID) LED

Buttons Power On/Off button,System Reset Button

Drive Bays

Drive Bays 12 x 3.5" hot-swap SAS/SATA drive bay with SES3, optional 2 x 2.5" hot-swap drive bay

Power Supply

920W Redundant Platinum Super Quiet power supply W/PMbus

Cooling System

3 x 8cm high-performance PWM fan(s),Optional 5 x 6cm 4pin high performance fan(s)

Form Factor

Form Factor : 2U Rackmount

Height : 3.5" (89 mm)

Width : 17.2" (437 mm)

Depth : 25.5" (647 mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com