

Tyrone Camarero Specifications

Tyrone

Camarero AD400TR-28RT

Key features

- EATX Server Board with dual Xeon Scalable processors
- Intel C622
- DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)
- 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards
- Intel® X557-AT2 dual 10GbE ports
- 10 SATA3 and six USB3.0 ports
- One M.2 2280 (SATA / PCIe compatible)
- 0 ~ 40 °C ambient operation temperature range
- Supports IPMI 2.0
- 8 x 3.5" hot-swap SAS3/SATA drive bay, 2 x 3.5" fixed drive bay
- 3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)
- 740/800W Redundant Power supply



Processor/Cache

Processor EATX Server Board with dual Xeon Scalable processors

Chipset

Chipset Intel C622

System Memory

Memory Capacity DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)

Expansion Slots

PCI-Express 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards

Integrated On-Board

SATA 10 x SATAIII (RAID 0,1,5,10)
LAN Intel I210AT; LAN2: Intel I210AT;
LAN3/4: Intel X557-AT2
IPMI Supports IPMI 2.0

Add-on Options

Raid Card Optional
Optical Drive Optional

Front Panel

Led's Power status LED, Hard drive activity LED, Network activity LEDs, System Information LED, Power fail LED
Buttons Power On/Off button, System Reset button

Drive Bays

HDD Bays 8 x 3.5" hot-swap SAS3/SATA drive bay, 2 x 3.5" fixed drive bay
Peripheral Drives Optional 1 x slim DVD-ROM drive bay, Optional 2 x USB 2.0 ports, Optional 1 x COM port tray, Optional 2 x USB 3.0 ports

Power Supply

740/800W Redundant Power supply

Cooling System

3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)

Form Factor

Form Factor 2U Rackmount
Height 3.5" (89 mm)
Width 17.2" (437 mm)
Depth 25.5" (647 mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com