

Tyrone Camarero Specifications

Tyrone

Camarero AD400TR-54i

Key features

- EATX Server Board with dual Xeon Scalable processors
- Intel C621
- DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)
- 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards
- LAN1: Intel I210AT , LAN2: Intel I210AT, 10/100/1000 Mbps, 2 x RJ-45
- 10 SATA3 and six USB3.0 ports
- One M.2 2280 (SATA / PCIe compatible)
- 0 ~ 40 °C ambient operation temperature range
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5
- Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 500 / 1200W Single power supply ,80 Plus platinum



Processor/Cache

Processor EATX Server Board with dual Xeon Scalable processors

Chipset

Chipset Intel C621

System Memory

Memory Capacity DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)

Expansion Slots

PCI-Express 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards

Integrated On-Board

SATA 10 x SATAIII (RAID 0,1,5,10)

LAN Intel I210AT; LAN2: Intel I210AT

Add-on Options

Raid Card Support RAID 0,1,5,6,10,50&60 Via optional AOC

Optical Drive Optional

Front Panel

Front Panel Front Control Panel Power Switch, System Reset

Buttons Power On/Off button

Drive Bays

Drive Bays External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5

Peripheral Drives Optional

Power Supply

500 / 1200W Single power supply ,80 Plus platinum

Cooling System

Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan

Form Factor

Form Factor : 5U Rackmount/tower/Convertible

Dimensions : 560 x 200 x 430 mm (22" x 7.9" x 16.9")

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com