

Tyrone Camarero Specifications



Camarero DII400TR-212RT

Key features

- Upto two 2nd Generation Intel® Xeon® Scalable processors, Socket P, TDP 165 W
- Intel C624 Chipset
- DDR4 ECC RDIMM/LRDIMM 2133/2400/2666/2933 & Intel® Optane™ DC Persistent Memory Supported, 24 DIMM Slots, 7.5 TB Max memory size
- 1GbE (mgmt port) + Dual Port RJ45 10GbE, 3 LAN Ports
- PCIe x4 Gen 3 1, PCIe x8 Gen 3 3 , PCIe x16 Gen 3 2
- 12 , 3.5 inch hot-swap drives
- 1300W single/redundant power supply .



Processor/Cache

Processor Upto two 2nd Generation Intel® Xeon® Scalable processors, Socket P, TDP 165 W

Chipset

Chipset Intel C624 Chipset

System Memory

Memory Capacity DDR4 ECC RDIMM/LRDIMM 2133/2400/2666/2933 & Intel® Optane™ DC Persistent Memory Supported 24 DIMM Slots, 7.5 TB Max memory size

Expansion Slots

PCI-Express PCIe x4 Gen 3 1, PCIe x8 Gen 3 3 , PCIe x16 Gen 3 2

Integrated On-Board

SATA 10, SW RAID 0, 1, 10, optional 5

LAN: t

Add-on Options

Raid Card Optional

Optical Drive None

Drive Bays

12 3.5" hot-swap drive tool less carriers

Power Supply

1300W single/redundant power supply .

Form Factor

Form Factor 2U, Spread Core Rack

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com