

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS40012E1-424RTL

Key features

- **Corporate Database, Database Processing & Storage, Database Processing & Storage, Enterprise Server, HPC, Data Center, iSCSI SAN**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- Intel® C622
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 3 PCI-E 3.0 x16, 4 PCI-E 3.0 x8, (slot 2 & 3 occupied by controller and JBOD expansion port)
- 24 Hot-swap 3.5" SAS3/SATA3 direct attached drive bays
- Broadcom 3008 SAS3 AOC
- 2x 10GBase-T LAN ports with Intel X557
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 3 Hot-swap 8cm redundant PWM cooling fans, 2 hot-swap 8cm rear exhaust PWM fans
- 1200W Redundant Power Supplies Titanium Level (96%)



Processor/Cache

Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
-----------	---

Chipset

Chipset	Intel® C622
---------	-------------

System Memory

Memory Capacity	Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
-----------------	--

Expansion Slots

PCI-Express	3 PCI-E 3.0 x16 slot, 4 PCI-E 3.0 x8 slots, (Slot 2 & 3 occupied by controller and JBOD Expansion Port)
-------------	---

Integrated On-Board

SAS	SAS3 (12Gbps) via Broadcom 3008 AOC, Broadcom 3008 controller
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10
LAN	2 RJ45 10GBase-T LAN ports, 1 RJ45 Dedicated IPMI LAN port

Add-on Options

Optical Drive	None
---------------	------

Front Panel

Led's	Power status LED, Hard drive activity LED, Network activity LEDs, System Overheat LED, Power fail LED
Buttons	Power On/Off button, System Reset button

Drive Bays

HDD bays	24 Hot-swap 3.5" SAS3/SATA3 drive bays
Optional	2 Optional Onboard NVMe M.2

Power Supply

	1200W Redundant Power Supplies Titanium Level (96%)
--	---

Cooling System

	3 Hot-swap 8cm redundant PWM cooling fans, 2 hot-swap 8cm rear exhaust PWM fans
--	---

Form Factor

Form Factor	4U Rackmount
Height-	7" (178mm),
Width-	17.2" (437mm),
Depth-	26.5" (673mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com