

# Tyrone Camarero Specifications

# Tyrone<sup>®</sup>

## Camarero DS4007R-216RTL

### Key features

- Corporate Database, Database Processing & Storage, Enterprise Server, HPC, Data Center. iSCSI SAN
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- Intel® C622
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 3 PCI-E 3.0 x16, 4 PCI-E 3.0 x8 (slot 1 occupied by controller)
- 16 Hot-swap 3.5" SAS3/SATA3 direct attached drive bays
- Broadcom 3108 SAS3 AOC
- 2x 10GBase-T LAN ports with Intel X722 + PHY Intel X557
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 3 Hot-swap 8cm redundant PWM fans
- 1600W Redundant Power Supplies Titanium Level (96%)



### Processor/Cache

Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
-----------	---

### Chipset

Chipset	Intel® C622
---------	-------------

### System Memory

Memory Capacity	Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
-----------------	--

### Expansion Slots

PCI-Express	3 PCI-E 3.0 x 16, 4 PCI-E 3.0 x 8 (slot 1 occupied by controller)
-------------	---

### Integrated On-Board

SAS	SAS3 (12Gbps) via Broadcom 3108 AOC; HW RAID, RAID 0, 1, 5, 6, 10, 50, 60
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10
LAN	2 RJ45 10GBase-T LAN ports, 1 RJ45 Dedicated IPMI LAN port

### Add-on Options

Optical Drive	None
---------------	------

### Front Panel

Led's	Power status LED, Hard drive activity LED, Network activity LEDs, System Overheat LED, Power fail LED
Buttons	Power On/Off button, System Reset button

### Drive Bays

HDD bays	16 Hot-swap 3.5" SAS3/SATA3 drive bays
Optional	2 Optional Onboard NVMe M.2

### Power Supply

	1600W Redundant Power Supplies Titanium Level (96%)
--	---

### Cooling System

	3 Hot-swap 8cm redundant PWM fans
--	-----------------------------------

### Form Factor

Form Factor	2U Rackmount
Dimensions	Width : 17.2" (437mm), Height : 3.5" (89mm), Depth : 27.75" (705 mm)

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit

[www.tyronesystems.com](http://www.tyronesystems.com)