

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

Camarero DS400TE1-224R4T

## Key features

- **Virtualization,Hyperconverge Storage,Cloud Computing,High End Enterprise Server**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.
- 2 PCI-E 3.0 x16 slots (FH, 10.5" L),4 PCI-E 3.0 x8 slots (FH, 10.5" L),1 PCI-E 3.0 x8 slot (LP)
- 4x 10GBase-T LAN ports via Intel X710
- 24 Hot-swap 2.5" drive bays:24 SAS3 via opt. AOC,(4 hybrid ports - opt. 4 NVMe), Optional 2 hot-swap 2.5" rear drive bays for SSDs;Optional M.2 NVMe and SATA3 ports
- VGA: Aspeed AST2500
- 4 Heavy duty 8cm PWM fans
- 1000W Redundant Power Supplies Titanium Level (96%)



Processor/Cache	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
Chipset	
Chipset	Intel® C621 chipset
System Memory	
Memory Capacity	Up to 6TB 3DS ECC RDIMM, DDR4-2933 MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.
Expansion Slots	
PCI-Express	2 PCI-E 3.0 x16 slots (FH, 10.5" L), 4 PCI-E 3.0 x8 slots (FH, 10.5" L), 1 PCI-E 3.0 x8 slot (LP)
Integrated On-Board	
SAS	SAS3 (12Gbps) via expander + Broadcom 3108/3008 AOC
LAN	4 RJ45 10GBase-T LAN ports, 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Optical Drive	None

Front Panel	
LED Indicators	Power status LED,HDD activity LED, Network activity LEDs,System information (overheat/UID) LED
Buttons	Power On/Off button,System Reset button
Drive Bays	
HDD Bays	24 Hot-swap 2.5" drive bays:24 SAS3 via opt. AOC (4 hybrid ports - opt. 4 NVMe)
M.2	M.2:1 M.2 PCI-E 3.0 x4 M-Key NVMe and 1 M.2 M-Key SATA3 via optional riser card RSC-UMR-8, cable CBL-SAST-0538 and plastic stand-off FST-SCRW-0074L (2240/2260/2280/22110),2 M.2 PCI-E 3.0 x4 M-Key NVMe via optional add-on card AOC-SLG3-2M2 (2260/2280/22110)
Power Supply	
1000W Redundant Power Supplies Titanium Level (96%)	
Cooling System	
4 Heavy duty 8cm PWM fans	
Form Factor	
Form Factor	2U Rackmount
Height	: 3.5" (89 mm),
Width	: 17.2" (437 mm),
Depth	: 27.76" (705.3 mm)
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	

© Intel, the Intel logo,the Intel Inside logo,Xeon,and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other Countries  
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners